

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
z	4K Starlight HDCVI IR Bullet Camera 1/2" Progressive Scan CMOS 15fps@4K, 20fps@6MP, 25/30fps@4MP 3.7-11mm motorized lens Max Aperture: F1.5 WDR(120dB), Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR Max. 4K resolution HD/SD switchable 1CH Audio In, built-in mic Max. IR length 80m, Smart IR IP67, DC12V±30%		27,400,000
2	4K Starlight HDCVI IR Bullet Camera 1/2" Progressive Scan CMOS 15fps@4K, 20fps@6MP, 25/30fps@4MP 3.6mm fixed lens Max Aperture: F1.6 WDR(120dB), Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR Max. 4K resolution HD/SD switchable 1CH Audio In, built-in mic Max. IR length 80m, Smart IR IP67, DC12V±30%		18,500,000
3	4K Starlight HDCVI IR Bullet Camera 1/2" Progressive Scan CMOS 15fps@4K, 20fps@6MP, 25/30fps@4MP 3.6mm fixed lens WDR(120dB), Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR Max. 4K resolution HD/SD switchable 1CH Audio In, built-in mic Max. IR length 40m, Smart IR IP67, DC12V±30%		15,700,000
4	6MP WDR HDCVI IR Bullet Camera 1/2.9" Progressive Scan CMOS 20fps@6MP, 25/30fps@4MP 2.7-13.5mm motorized lens Max Aperture: F1.3 WDR(120dB), Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR Max. 6MP resolution HD/SD switchable 1CH Audio In, built-in mic Max. IR length 80m, Smart IR IP67, DC12V±30%		21,000,000
5	6MP WDR HDCVI IR Bullet Camera 1/2.9" Progressive Scan CMOS 20fps@6MP, 25/30fps@4MP 3.6mm fixed lens Max Aperture: F1.9 WDR(120dB), Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR Max. 6MP resolution HD/SD switchable 1CH Audio In, built-in mic Max. IR length 40m, Smart IR IP67, DC12V±30%		14,400,000
6	1/3" 4.1Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 2.7-13.5mm vari-focal lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable OSD Menu Max. IR length 60m, Smart IR IP67, DC12V		12,600,000

02146083954

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
7	DH-HAC-HFW1400DP 1/3" 4.1Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 3.6mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable OSD Menu Max. IR length 80m, Smart IR IP67, DC12V		9,300,000
8	DH-HAC-HFW1400BP 1/3" 4Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 3.6mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable OSD Menu Max. IR length 50m, Smart IR IP67, DC12V		8,400,000
9	DH-HAC-HFW1400SP 1/3" 4.1Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 3.6mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable OSD Menu Max. IR length 30m, Smart IR IP67, DC12V		7,300,000
10	DH-HAC-HFW1400TP 1/3" 4.1Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 3.6mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable OSD Menu Max. IR length 25m, Smart IR IP67, DC12V		7,100,000
11	DH-HAC-ME1400B-PIR 4MP HDCVI MotionEye Camera 1/3" 4.1Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 2.8mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR 10m/110°detecting range/angle HD and SD output switchable OSD Menu Max. IR length 20m, Smart IR IP67, DC12V		8,100,000
12	DH-HAC-B1A41P Cooper Series NEW Product 4MP HDCVI IR Bullet Camera 1/2.7" 4Megapixel CMOS 25/30fps@4MP,25/30fps@1080P 3.6mm fixed lens HD and SD output switchable Max. IR length 20m IP67, DC12V Casing: Plastic		5,400,000
13	DH-HAC-B2A41P Cooper Series NEW Product 4MP HDCVI IR Bullet Camera 1/2.7" 4Megapixel CMOS 25/30fps@4MP,25/30fps@1080P 3.6mm fixed lens HD and SD output switchable Max. IR length 20m IP67, DC12V Casing: Aluminium		5,900,000
14	DH-HAC-HFW2231RP-Z-IRE6 1/2.8" 2.1Megapixel CMOS, (Starlight) 25/30fps@1080P, 25/30fps@720P 2.7-13.5mm Motorized lens WDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR HD and SD output switchable OSD Menu Max. IR length 60m, Smart IR IP67, DC12V		18,800,000
15	DH-HAC-HFW2231EP 1/2.8" 2.1Megapixel CMOS (Starlight) 25/30fps@1080P, 25/30fps@720P 3.6mm Fixed lens WDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR HD and SD output switchable OSD Menu Max. IR length 40m, Smart IR IP67, DC12V		11,500,000

توجه: دستگاه های جدید XVR (به جز دستگاه های ستاره دار)، دوربین هایی که میکروفون داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.

02146083954

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
16	DH-HAC-HFW2231DP 1/2.8" 2.1Megapixel CMOS (Starlight) 25/30fps@1080P, 25/30fps@720P 3.6mm Fixed lens WDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR HD and SD output switchable OSD Menu Max. IR length 80m, Smart IR IP67, DC12V		12,500,000
17	DH-HAC-HFW1230DP NEW Product 1/2.8" 2Megapixel CMOS (Starlight) 25/30fps@1080P, 25/30fps@720P 3.6mm Fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable OSD Menu Max. IR length 80m, Smart IR IP67, DC12V		7,600,000
18	DH-HAC-HFW1220RP-VF-IRE6 1/2.9" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 2.7-12mm vari-focal lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 60m, Smart IR IP67, DC12V		10,500,000
19	DH-HAC-HFW1220DP 1/2.9" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 80m, Smart IR IP67, DC12V		6,900,000
20	DH-HAC-HFW1220BP 1/2.9" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 50m, Smart IR IP67, DC12V		6,400,000
21	DH-HAC-HFW1220SP 1/2.9" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 30m, Smart IR IP67, DC12V		5,150,000
22	DH-HAC-HFW1200TLP NEW Product 1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 40m, Smart IR IP67, DC12V		4,800,000
23	DH-HAC-HFW1200DP 1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P DWDR, Day/Night(ICR), AWB, AGC, HLC, BLC, 2D-DNR HD and SD output switchable 3.6mm fixed lens Max. IR LEDs length 80m, Smart IR IP67, DC12V		6,650,000
24	DH-HAC-HFW1200BP 1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P DWDR, Day/Night(ICR), AWB, AGC, HLC, BLC, 2D-DNR HD and SD output switchable 3.6mm fixed lens Max. IR LEDs length 50m, Smart IR IP67, DC12V		6,100,000

توجه: دستگاه های جدید XVR (به جز دستگاه های ستاره دار)، دوربین هایی که میکروفون داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.

02146083954










مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
25	DH-HAC-HFW1200SP 1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens HD and SD output switchable DWDR, Day/Night(ICR), AWB, AGC, BLC,HLC, 2DNR , Support OSD Menu Max. IR length 30m, Smart IR IP67, DC12V		4,950,000
26	DH-HAC-HFW1200SLP 1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens HD and SD output switchable DWDR, Day/Night(ICR), AWB, AGC, BLC,HLC, 2DNR , Support OSD Menu Max. IR length 30m, Smart IR IP67, DC12V		4,000,000
27	DH-HAC-HFW1200TP 1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens HD and SD output switchable DWDR, Day/Night(ICR), AWB, AGC, BLC,HLC, 2DNR , Support OSD Menu Max. IR length 25m, Smart IR IP67, DC12V		4,600,000
28	DH-HAC-HFW1200TP-A 1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens Built-in mic HD and SD output switchable DWDR, Day/Night(ICR), AWB, AGC, BLC,HLC, 2DNR , Support OSD Menu Max. IR length 30m, Smart IR IP67. DC12V NEW Product		5,300,000
29	DH-HAC-HFW1200RMP-0360B 1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens HD and SD output switchable Day/Night(ICR), AWB, AGC, BLC, 2D-DNR , Support OSD Menu Max. IR length 20m, Smart IR IP67, DC12V Metal Case		4,200,000
30	DH-HAC-ME1200BP-PIR 2MP HDCVI MotionEye Camera 1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 2.8mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR 10m/110°detecting range/angle HD and SD output switchable OSD Menu Max. IR length 20m, Smart IR IP67, DC12V		6,000,000
31	DH-HAC-HUM1220AP 2MP HDCVI MotionEye Camera 1/2.9" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 2.8mm fixed lens HD and SD output switchable DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR , Support OSD Menu 12m/100°detecting range/angle Two level(jumper) detection sensitivity adjustable Built-in tamper switch		7,500,000
32	DH-HAC-B2A21P 1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens HD and SD output switchable DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR , Support OSD Menu Max. IR length 20m, Smart IR IP67, DC12V Casing: Aluminium Cooper Series NEW Product		3,850,000
33	DH-HAC-B1A21P 1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens HD and SD output switchable DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR , Support OSD Menu Max. IR length 20m, Smart IR IP67, DC12V Casing: Plastic Cooper Series NEW Product		3,300,000











توجه: دستگاه های جدید XVR (به جز دستگاه های ستاره دار)، دوربین هایی که میکروفون داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.

02146083954

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
34	DH-HAC-HUM3201B 1/2.8" 2Megapixel CMOS(Starlight) 25/30fps@1080P, 25/30fps@720P 2.8mm fixed lens HD and SD output switchable WDR(120dB), Day/Night(ICR), AWB, AGC, BLC,HLC, 3DNR , Support OSD Menu DC12V		9,300,000
35	DH-HAC-HFW1100RP-VF 1/2.9" 1Megapixel CMOS 25/30fps@720P Day/Night(ICR), AWB, AGC, BLC, 2DNR 2.7~12mm vari-focal lens Max. IR LEDs length 30m, Smart IR IP67, DC12V		5,200,000
36	DH-HAC-HFW1100SP 1/3" 1Megapixel CMOS 25/30fps@720P 3.6mm fixed lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC,HLC, 2DNR Max. IR LEDs length 30m, Smart IR IP67, DC12V		3,400,000
37	DH-HAC-HFW1100SL 1/3" 1Megapixel CMOS 25/30fps@720P 3.6mm fixed lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC,HLC, 2DNR Max. IR LEDs length 30m, Smart IR IP67, DC12V		2,800,000
38	DH-HAC-HFW1100RMP-0280B Metal Case 1/2.9" 1Megapixel CMOS 25/30fps@720P Day/Night(ICR), AWB, AGC, BLC, 2DNR 2.8mm fixed lens Max. IR LEDs length 20m, Smart IR IP67, DC12V		2,900,000
39	DH-HAC-HFW1100RMP-0360B Metal Case 1/2.9" 1Megapixel CMOS 25/30fps@720P Day/Night(ICR), AWB, AGC, BLC, 2DNR 3.6mm fixed lens Max. IR LEDs length 20m, Smart IR IP67, DC12V		2,900,000
40	DH-HAC-HFW1100RP 1/3" 1Megapixel CMOS 25/30fps@720P 3.6mm fixed lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, 2DNR Max. IR LEDs length 20m, Smart IR IP67, DC12V		2,500,000
41	DH-HAC-HDW2802TP-A 4K Starlight HDCVI IR Eyeball Camera 1/2" Progressive Scan CMOS 15fps@4K, 20fps@6MP, 25/30fps@4MP 3.6mm fixed lens Max Aperture: F1.6 WDR(120dB), Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR Max. 4K resolution HD/SD switchable 1CH Audio In, built-in mic Max. IR length 50m, Smart IR IP67, DC12V±30%		15,700,000
42	DH-HAC-HDW2601TP-Z-A 6MP WDR HDCVI IR Eyeball Camera 1/2.9" Progressive Scan CMOS 20fps@6MP, 25/30fps@4MP 2.7-13.5mm motorized lens Max Aperture: F1.3 WDR(120dB), Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR Max. 6MP resolution HD/SD switchable 1CH Audio In, built-in mic Max. IR length 60m, Smart IR IP67, DC12V±30%		21,000,000









توجه: دستگاه های جدید XVR(به جز دستگاه های ستاره دار)، دوربین هایی که میکروفون داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
43	6MP WDR HDCVI IR Eyeball Camera 1/2.9" Progressive Scan CMOS 20fps@6MP, 25/30fps@4MP 3.6mm fixed lens Max Aperture: F1.9 WDR(120dB), Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR Max. 6MP resolution HD/SD switchable 1CH Audio In, built-in mic Max. IR length 50m, Smart IR IP67, DC12V±30%		14,400,000
44	1/3" 4.1Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 2.7-13.5mm Varifocal lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable OSD Menu Max. IR length 30m, Smart IR IP67, IK10, DC12V		13,600,000
45	1/3" 4.1Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 3.6mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable Built-in Mic OSD Menu Max. IR length 50m, Smart IR IP67, DC12V		8,100,000
46	1/3" 4.1Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 3.6mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable OSD Menu Max. IR length 50m, Smart IR IP67, DC12V		7,400,000
47	1/3" 4.1Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 3.6mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable OSD Menu Max. IR length 30m, Smart IR IP67, DC12V		6,900,000
48	1/2.7" 4Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P 3.6mm fixed lens HD and SD output switchable Max. IR length 20m IP67, DC12V Casing: Aluminium		5,900,000
	Cooper Series NEW Product		
49	1/2.7" 4Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P 3.6mm fixed lens HD and SD output switchable Max. IR length 20m DC12V Casing: Plastic		5,300,000
	Cooper Series NEW Product		
50	1/2.8" 2.1Megapixel CMOS (Starlight) 25/30fps@1080P, 25/30fps@720P 3.6mm Fixed lens WDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR HD and SD output switchable OSD Menu Max. IR length 20m, Smart IR IP67, IK10, DC12V		11,900,000
51	1/2.8" 2.1Megapixel CMOS (Starlight) 25/30fps@1080P, 25/30fps@720P 3.6mm Fixed lens WDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR HD and SD output switchable OSD Menu Max. IR length 50m, Smart IR IP67, DC12V		11,500,000

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
52	DH-HAC-HDBW1220RP-VF 1/2.9" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 2.7-12mm vari-focal lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 30m, Smart IR IP67, IK10, DC12V		9,800,000
53	DH-HAC-HDW1220EMP-A  1/2.9" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens Built-in Mic HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 50m, Smart IR IP67, DC12V		5,940,000
54	DH-HAC-HDW1220MP 1/2.9" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 30m, Smart IR IP67, DC12V		4,750,000
55	HAC-HDPW1200R 1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 30m, Smart IR DC12V		4,000,000
56	DH-HAC-HDW1200SLP 1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 2.8mm fixed lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 20m, Smart IR IP67, DC12V		3,700,000
57	DH-HAC-HDW1200LP 2MP HDCVI IR Eyeball Camera 1/2.7" 2Megapixel CMOS Max 30fps@1080P 2.1mm fixed lens HD and SD output switchable Built in Mic Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 3m, Smart IR IP67, DC12V		7,600,000
58	DH-HAC-HDW1200MP 1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens HD and SD output switchable Day/Night(ICR), AWB, AGC, BLC, 2D-DNR , Support OSD Menu Max. IR length 30m, Smart IR IP67, DC12V		4,500,000
59	DH-HAC-HDW1200EMP-A  Metal Case 1/2.7" 2Megapixel CMOS 25/30fps@1080P Built-in MIC Day/Night(ICR), AWB, AGC, BLC, 2DNR 3.6mm fixed lens (6mm optional) Max. IR LEDs length 50m, Smart IR IP67, DC12V		5,800,000






توجه: دستگاه های جدید XVR (به جز دستگاه های ستاره دار)، دوربین هایی که میکروفون داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.

02146083954

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
60 DH-HAC-T2A21P Cooper Series NEW Product	1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 2.8mm fixed lens HD and SD output switchable DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR , Support OSD Menu Max. IR length 20m, Smart IR IP67, DC12V Casing: Aluminium		3,800,000
61 DH-HAC-T1A21P Cooper Series NEW Product	1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens HD and SD output switchable DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR , Support OSD Menu Max. IR length 20m, Smart IR Casing: Plastic DC12V		3,300,000
62 DH-HAC-HDW1100MP-0360B	1/3" 1Megapixel CMOS 25/30fps@720P 3.6mm fixed lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC,HLC, 2DNR Max. IR LEDs length 30m, Smart IR IP67, DC12V		2,700,000
63 DH-HAC -HDW1100RP-0360B	1/3" 1Megapixel CMOS 25/30fps@720P 3.6mm fixed lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC,HLC, 2DNR Max. IR LEDs length 20m, Smart IR IP67. DC12V		2,600,000
64 SD22204I-GC	Powerful 4x optical zoom (2.7mm~11mm) Max. 25/30fps@1080P, 50/60fps@720P resolution WDR, Day/Night (ICR), DNR (2D&3D), Auto iris, Auto focus, AWB, AGC, BLC Max 100°/s pan speed HD & SD Switchable Up to 300 presets, 5 auto scan, 8 tour, 5 pattern 1/2.8" 2Megapixel Exmor R CMOS (Starlight) Max 25/30fps @1080P & 20/30/50/60fps @720P Resolution 4.8mm ~ 120mm 25x optical zoom WDR (120db), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus Max 400°/s pan speed, 360° endless pan rotation		20,100,000
65 DH-SD59225I-HC-S2	Control over coaxial cable 1-channel BNC HDCVI/CVBS output (switchable) Up to 300 presets, 5 auto scan, 8 tour, 5 pattern Built-in 2/1 Alarm in/out 1 Audio Input , RS485 IR Distance up to 150m IP66,OSD		85,000,000
66 SD59230I-HC	2MP 30x Starlight IR PTZ HDCVI Camera 1/2.8" Exmor R CMOS Max. 25/30fps @1080P(1920x1080) & 20/30/50/60fps @720Presolution 4.5mm~135mm 30x optical zoom WDR(120dB), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus Max 400°/s pan speed, 360° endless pan rotation HD and SD switchable Up to 300 presets, 5 auto scan, 8 tour, 5 pattern Audio(in/out) 1 / 1 Built-in 2/1 Alarm in/out IR Distance up to 150m IP66.OSD		11,310,000
67 DH-SD49225I-HC	2MP 25x Starlight IR PTZ HDCVI Camera 1/2.8" STARVIS CMOS Max. 25/30fps @1080P(1920x1080) & 20/30/50/60fps @720P Resolution 4.8mm~120mm 25x optical zoom WDR(120dB), Day/Night(ICR), Ultra DNR, HLC, BLC, Auto iris, Auto focus Max 400°/s pan speed, 360° endless pan rotation HD and SD switchable Up to 300 presets, 5 auto scan, 8 tour, 5 pattern 2/1 Alarm In/Out 1CH Audio In RS485 IR Distance up to 100m		63,800,000

توجه: دستگاه های جدید XVR(به جز دستگاه های ستاره دار)، دوربین هایی که میکروفون داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.




مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
68 DH-XVR1A04  	4CH Penta-brid 1080N/720P Real-Time Cooper Recorder H.264 video compression 4CH: 1/4 Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [4+1 IP up to 2 Megapixel(20 Mbps)] 1 Audio Input / 1 Audio Output 1 SATA Port , Up to 6 TB HDMI , VGA ,simultaneous video Output 2*USB 2.0 10/100 Mbps LAN Interface P2P Support		8,300,000
69 DH-XVR1B04H  	4CH Penta-brid 4M-N/1080P None Real-Time Cooper Recorder H.265+/H.265 dual-stream video compression 4CH: 1/4 Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [4+2 IP up to 6 Megapixel(24 Mbps)] 1 Audio Input / 1 Audio Output 1 SATA Port , Up to 6 TB HDMI , VGA ,simultaneous video Output 2*USB 2.0 10/100 Mbps LAN Interface P2P Support		10,900,000
70 DH-XVR1A08  	8CH Penta-brid 1080N/720P noneReal-Time Cooper Recorder H.264 video compression 8CH:1/4/9 Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [8+2 IP up to 5 Megapixel(40 Mbps)] 1 Audio Input / 1 Audio Output 1 SATA Port , Up to 6 TB HDMI , VGA ,simultaneous video Output 2*USB 2.0 10/100 Mbps LAN Interface P2P Support		10,900,000
71 DH-XVR1B08H  	8CH Penta-brid 4M-N/1080P None Real-Time Cooper Recorder H.265+/H.265 dual-stream video compression 8CH: 1/4/8 Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [8+4 IP up to 6 Megapixel(48 Mbps)] 1 Audio Input / 1 Audio Output 1 SATA Port , Up to 6 TB HDMI , VGA ,simultaneous video Output 2*USB 2.0 10/100 Mbps LAN Interface P2P Support		17,100,000
72 DHI-XVR4104HS-S2 	4CH Penta-brid 1080N/720P Real-Time Recorder H.264 video compression 4CH: 1/4 Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [4+1 IP up to 2 Megapixel(20 Mbps)] 1 Audio Input / 1 Audio Output 1 SATA Port , Up to 8 TB HDMI , VGA ,simultaneous video Output RS485 for PTZ support 2*USB 2.0 10/100 Mbps LAN Interface P2P Support		9,300,000
73 DHI-XVR5104HS-S2 	4CH Penta-brid 4M-N/1080P Non-real Time , 1080N/720P Real-Time Recorder 4M-N/1080P@15fps , 1080N/720P@25fps H.264+/H.264 dual-stream video compression 4CH: 1/4 Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [4+2 IP up to 5 Megapixel(24 Mbps)] Support Smart Search and Intelligent Video System 1 Audio Input / 1 Audio Output 1 SATA Port , Up to 8 TB HDMI , VGA ,simultaneous video Output RS485 for PTZ support 2*USB 2.0 10/100 Mbps LAN Interface		11,900,000
74 DHI-XVR5104HS-4M 	4CH Penta-brid 4MP Non-real Time , 1080P Real-Time Recorder H.264+/H.264 dual-stream video compression 4CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [4+2 IP up to 5 Megapixel(24 Mbps)] Support Smart Search and Intelligent Video System 1/1 Audio In/Out 1 SATA Port , Up to 8 TB 1*HDMI(2K) ,1* VGA ,simultaneous video Output RS485 for PTZ support 2*USB 2.0 10/100 Mbps LAN Interface P2P Support		17,600,000

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
75	<p>DH-XVR5104HS-X1</p> <p>NEW Product</p> <p>★</p> <p>4CH Penta-brid 4MP-N/1080P Non-real Time , 1080N/720P Real-Time Recorder H.265+/H.265 dual-stream video compression Record Rate: 1st channel 5M-N(1~10fps), other channels 4M-N/1080P(1~15fps); 1080N/720P/960H/ D1/CIF (1~25/30fps) 4CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [4+2 IP up to 6 Megapixel(24 Mbps)] Support Smart Search and Intelligent Video System 1/1 Audio In/Out 1 SATA Port , Up to 8 TB 1*HDMI,1* VGA simultaneous video Output RS485 for PTZ support 2*USB 2.0 , 10/100 Mbps LAN Interface , P2P Support</p>		12,600,000
76	<p>DH-XVR5104HS-4KL-X</p> <p>★</p> <p>4CH Penta-brid 4K Recorder 4K@7fps,6MP@10fps,5MP@12fps,4MP@15fp,4M-N/1080P/720P@25fps H.265+/H.265 dual-stream video compression 4CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [4+2 IP up to 8 Megapixel(24 Mbps)] Support Smart Search and Intelligent Video System 1/1 Audio In/Out 1 SATA Port , Up to 10 TB 1*HDMI(4K) , 1*VGA ,simultaneous video Output RS485 for PTZ support 2*USB 2.0 1*10/100 Mbps LAN Interface P2P Support</p>		18,500,000
77	<p>DHI-XVR4108HS-S2</p> <p>★</p> <p>8CH Penta-brid 1080N/720P noneReal-Time Recorder H.264 video compression 8CH: 1/4/9 Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [8+2 IP up to 5 Megapixel(40 Mbps)] 1 Audio Input / 1 Audio Output 1 SATA Port , Up to 8 TB HDMI , VGA ,simultaneous video Output RS485 for PTZ support 2*USB 2.0 10/100 Mbps LAN Interface P2P Support</p>		12,200,000
78	<p>DHI-XVR5108HS-S2</p> <p>★</p> <p>8CH Penta-brid 4M-N/1080P Non-real Time , 1080N/720P Real-Time Recorder 4M-N/1080P@15fps , 1080N/720P@25fps H.264+/H.264 dual-stream video compression 8CH:1/4/9 Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [8+4 IP up to 5 Megapixel(48 Mbps)] Support Smart Search and Intelligent Video System 1 Audio Input / 1 Audio Output 1 SATA Port , Up to 8 TB HDMI , VGA ,simultaneous video Output RS485 for PTZ support 2*USB 2.0 10/100 Mbps LAN Interface P2P Support</p>		19,700,000
79	<p>DH-XVR5108HS-X1</p> <p>NEW Product</p> <p>★</p> <p>8CH Penta-brid 4MP-N/1080P Non-real Time , 1080N/720P Real-Time Recorder H.265+/H.265 dual-stream video compression Record Rate: 1st & 2nd channels 5M-N(1~10fps), other channels 4M-N/1080P(1~15fps); 1080N/720P/960H/ D1/CIF (1~25/30fps) 8CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [8+4 IP up to 6 Megapixel(24 Mbps)] Support Smart Search and Intelligent Video System 1/1 Audio In/Out 1 SATA Port , Up to 8 TB 1*HDMI,1* VGA simultaneous video Output RS485 for PTZ support 2*USB 2.0</p>		20,500,000

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
80	<p>DH-XVR5108HS-X</p> <p>8CH Penta-brid 1080P None-Real time Recorder 5M-N@10fps, 4M-N/1080P@15fps, 1080N/720P@25fps H.265+/H.265/H.264+/H.264 dual-stream video compression 8CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [8+4 IP up to 6 Megapixel(48 Mbps)] Support Smart Search and Intelligent Video System 1/1 Audio In/Out 1 SATA Port , Up to 10 TB 1*HDMI, 1*VGA ,simultaneous video Output RS485 for PTZ support 2*USB 2.0 1*10/100 Mbps LAN Interface , P2P Support</p>		21,100,000
81	<p>DHI-XVR5108H-4KL</p> <p>8CH Penta-brid 4K Recorder 4K@7fps, 4MP@15fp , 1080P/720P@25fps H.264+/H.264 dual-stream video compression 8CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [8+4 IP up to 8 Megapixel(48 Mbps)] Support Smart Search and Intelligent Video System 1/1 Audio In/Out 1 SATA Port , Up to 8 TB 1*HDMI(4K) , 1*VGA ,simultaneous video Output RS485 for PTZ support 2*USB 2.0 1*10/100/1000 Mbps LAN Interface</p>		25,100,000
82	<p>DH-XVR5108H-4KL-X</p> <p>8CH Penta-brid 4K Recorder 4K@7fps,6MP@10fps,5MP@12fps,4MP@15fp,4M-N/1080P/720P@25fps H.265+/H.265 dual-stream video compression 1/4CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [8+4 IP up to 8 Megapixel(48 Mbps)] Support Smart Search and Intelligent Video System 1/1 Audio In/Out 1 SATA Port , Up to 10 TB 1*HDMI(4K) , 1*VGA ,simultaneous video Output RS485 for PTZ support 2*USB 2.0 1*10/100/1000 Mbps LAN Interface P2P Support</p>		27,900,000
83	<p>DH-XVR1B16H</p> <p>Cooper Series</p> <p>16CH Penta-brid 4M-N/1080P None Real-Time Cooper Recorder H.265+/H.265 dual-stream video compression 16CH: 1/4/8/16 Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [16+8 IP up to 6 Megapixel(96 Mbps)] 1 Audio Input / 1 Audio Output 1 SATA Port , Up to 6 TB HDMI , VGA ,simultaneous video Output 1 USB 2.0 , 1 USB 3.0 10/100/1000 Mbps LAN Interface</p>		28,500,000
84	<p>DH-XVR4116HS-X</p> <p>16CH Penta-brid 1080N/720P NoneReal-Time Recorder H.265/H.264 video compression 16CH: 1/4/9/16 Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [16+2 IP up to 6 Megapixel(72 Mbps)] 1 Audio Input / 1 Audio Output 1 SATA Port , Up to 10 TB HDMI , VGA ,simultaneous video Output RS485 for PTZ support 2*USB 2.0 10/100 Mbps LAN Interface</p>		24,500,000
85	<p>DHI-XVR4116HS-S2</p> <p>16CH Penta-brid 1080N/720P noneReal-Time Recorder H.264 video compression 16CH: 1/4/9/16 Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [16+2 IP up to 5 Megapixel(72 Mbps)] 1 Audio Input / 1 Audio Output 1 SATA Port , Up to 8 TB HDMI , VGA ,simultaneous video Output RS485 for PTZ support 2*USB 2.0 10/100 Mbps LAN Interface</p>		21,200,000

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
86	<p>DH-XVR5116H-X</p> <p>16CH Penta-brid 1080P None-Real time Recorder 5M-N@10fps, 4M-N/1080P@15fps, 1080N/720P@25fps H.265+/H.265/H.264+/H.264 dual-stream video compression 16CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [16+8 IP up to 6 Megapixel(96 Mbps)] Support Smart Search and Intelligent Video System 1/1 Audio In/Out 1 SATA Port , Up to 10 TB 1*HDMI, 1*VGA ,simultaneous video Output RS485 for PTZ support 2*USB(1 USB2.0 , 1 USB3.0) 1*10/100/1000 Mbps LAN Interface</p>		34,300,000
87	<p>DH-XVR5216AN-S2</p> <p>16CH Penta-brid 4M-N/1080P Non-real Time , 1080N/720P Real-Time Recorder 4M-N/1080P@15fps , 1080N/720P@25fps H.264+/H.264 dual-stream video compression 1/4/9/16CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [16+8 IP up to 5 Megapixel(96 Mbps)] Support Smart Search and Intelligent Video System 1/1 Audio In/Out 2 SATA Port , Up to 16 TB HDMI , VGA ,simultaneous video Output RS485 for PTZ support 2 USB Ports (1 USB 2.0 , 1 USB 3.0) 10/100/1000 Mbps LAN Interface</p>		36,500,000
88	<p>DH-XVR5216AN-X</p> <p>16CH Penta-brid 1080P None-Real time Recorder 5M-N@10fps, 4M-N/1080P@15fps, 1080N/720P@25fps H.265+/H.265/H.264+/H.264 dual-stream video compression 16CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [16+8 IP up to 6 Megapixel(96 Mbps)] Support Smart Search and Intelligent Video System 1/1 Audio In/Out 2 SATA Port , Up to 10 TB 1*HDMI, 1*VGA ,simultaneous video Output RS485 for PTZ support 2*USB(1 USB2.0 , 1 USB3.0) 1*10/100/1000 Mbps LAN Interface P2P Support</p>		39,800,000
89	<p>DHI-XVR5216AN-4KL</p> <p>16CH Penta-brid 4K Recorder 4K@7fps, 4MP@15fp , 1080P/720P@25fps H.264+/H.264 dual-stream video compression 16CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [16+8 IP up to 8 Megapixel(96 Mbps)] Support Smart Search and Intelligent Video System 1/1 Audio In/Out 2 SATA Port , Up to 16 TB 1*HDMI(4K) , 1*VGA ,simultaneous video Output RS485 for PTZ support 2*USB 2.0 1*10/100/1000 Mbps LAN Interface</p>		49,500,000
90	<p>DH-XVR5216AN-4KL-X</p> <p>16CH Penta-brid 4K Recorder 4K@7fps,6MP@10fps,5MP@12fps,4MP@15fp,4M-N/1080P/720P@25fps H.265+/H.265/H.264+/H.264 dual-stream video compression 16CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [16+8 IP up to 8 Megapixel(96 Mbps)] Support Smart Search and Intelligent Video System 1/1 Audio In/Out 2 SATA Port , Up to 10 TB 1*HDMI(4K), 1*VGA ,simultaneous video Output RS485 for PTZ support 2*USB(1 USB2.0 , 1 USB3.0) 1*10/100/1000 Mbps LAN Interface P2P Support</p>		54,500,000

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
91	<p>DH-XVR5416L</p> <p>16CH Penta-brid 1080N/720P Real-Time, 1080P None-Real time Recorder H.264+/H.264 dual-stream video compression 1/4/9/16CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [16+8 IP up to 5 Megapixel(96Mbps)] 4 Audio IN / 1 Audio Out 16 Alarm IN / 6 Alarm Out 4 SATA Port , Up to 6 TB 1 e-SATA 2*HDMI , VGA , TV simultaneous video Output RS485 , RS 232 2 USB 3.0, 1 USB 2.0 10/100/1000 Mbps LAN Interface , P2P Support</p>		72,000,000
92	<p>DH-HCVR8816S-S3</p> <p>All channel 1080P realtime recording Support HDCVI/AHD/Analog/IP Video input H.264 dual-stream video compression 16 channel synchronous realtime playback Tribrid (IP+CVI+Analogue)N+M[16+48 up to 12Megapixel(384Mbps)] 16 Audio Input , 1 Audio Output 16*Alarm Input , 6*Relay Output 8 SATA ports, up to 64TB, 1 eSATA 2 HDMI(HDMI1 up to 4K), 1 VGA, 1 TV HDMI 1/VGA simultaneous video output,HDMI2/VGA(HDMI1) independent video output RS485 , PTZ Support 4 ports (2 Rear USB3.0, 2 Front USB2.0) 2*10/100/1000 Mbps LAN Interface IVS: Tripwire, Intrusion, Abandoned/Missing, Scene Change, Face Detection, People Counting, Smart Tracking P2P Support</p>		Call
93	<p>DH-XVR5232AN-S2</p> <p>32CH Penta-brid 4M-N/1080P Non-real Time , 1080N/720P Real-Time Recorder 4M-N/1080P@15fps , 1080N/720P@25fps H.264+/H.264 dual-stream video compression 16CH:1/4/9/16CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [32 IP up to 5 Megapixel(128 Mbps)] Support Smart Search and Intelligent Video System 1/1 Audio In/Out 2 SATA Port , Up to 16 TB HDMI , VGA , 1TV video Output RS485 for PTZ support 2 USB Ports (1 USB 2.0 , 1 USB 3.0)</p>		66,500,000
94	<p>DH-XVR5232AN-X</p> <p>32CH Penta-brid 1080P Recorder 5M-N@10fps, 4M-N/1080P@15fps, 1080N/720P@25fps H.265+/H.265/H.264+/H.264 dual-stream video compression 16CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS)[32 IP up to 6 Megapixel(128 Mbps)] Support Smart Search and Intelligent Video System 1/1 Audio In/Out 2 SATA Port , Up to 10 TB 1*HDMI(4K), 1*VGA ,simultaneous video Output RS485 for PTZ support 2*USB(1 USB2.0 , 1 USB3.0) 1*10/100/1000 Mbps LAN Interface P2P Support</p>		69,800,000
95	<p>DH-XVR5432L</p> <p>32CH Penta-brid 1080P None-Real time, 1080N/720P Real-Time Recorder H.264+/H.264 dual-stream video compression 1/4/9/16CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS)[32 IP up to 5 Megapixel(128Mbps)] 4 Audio IN / 1 Audio Out 16 Alarm IN / 6 Alarm Out 4 SATA Port , Up to 8 TB 1 e-SATA Port 2 HDMI, 1 VGA, 1 TV RS485 , RS232, RS422 2 USB 3.0, 1 USB 2.0 10/100/1000 Mbps LAN Interface Smart Search and Intelligent Video System P2P Support</p>		

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
96	<p>DH-XVR5832S</p> <p>32CH Penta-brid 1080P None-Real time, 1080N/720P Real-Time Recorder H.264+/H.264 dual-stream video compression 1/4/9/16CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS)[32 IP up to 5 Megapixel(128Mbps)] 16 Audio IN / 1 Audio Out 16 Alarm IN / 6 Alarm Out 8 SATA Port , Up to 8 TB 1 e-SATA Port 2 HDMI, 1 VGA, 1 TV RS485 , RS232, RS422 2 USB 3.0, 2 USB 2.0 10/100/1000 Mbps LAN Interface Smart Search and Intelligent Video System P2P Support</p>		
97	<p>PFT2100</p> <p>HDMI-HDCVI Converter *Input HDMI video signal, self-adaptive output HDCVI signal *HDMI support mode, 1024*768@60Hz, 1280*720@50/60Hz, 1280*1024@60Hz, 1600*1200@60Hz, 1920*1080@50/60Hz *HDCVI output format, 720P/50, 720P/60, 1080P/25, 1080P/30 *Output Cable Length 1080P: 75-5 coaxial cable support 300m/720P: 75-5 coaxial cable support 500m *Power:DC12V</p>		9,100,000
98	<p>TP2105</p> <p>HDCVI Video Converter real time non-compression transmission *Input: 1*HDCVI (BNC) *Output: 1*HDCVI (BNC), 1*CVBS (BNC), 1*HDMI, 1*VGA *1080p/720p: 75-5 coaxial support 100m Input Transmission Distance *1080p/720p: 75-5 coaxial support 100m HDCVI Output Transmission Distance *Support 2 dial switches and indicate 4 Baud rate: 2400b/s, 4800b/s, 9600b/s and 115200b/s *RS485</p>		9,700,000
99	<p>PFM801</p> <p>*1 Channel HDCVI Transmission Signal *720P, 400M(max); 1080P, 200M(max)Transmission Distance *Input voltage DC24-36V, can provide DC12V8W(max) power supply to remote cameras *Use single UTP (CAT-5E and CAT-6) real-time transmit 1-ch HD video signal and 1-ch DC power *Excellent anti-thunder, anti-static and anti-interference capabilities *Compatible with HDCVI/TVI/AHD format</p>		1,200,000
100	<p>DH-PFM900-E</p> <p>4" IPS screen and QWERTY flip keyboard with 45keys Support H.264/H.265 HD decoding protocol Support IP,HDCVI/AHD/TVI/CVBS Support IP configuration via Onvif protocol Support audio and RS485 control Support TDR network cable test and digital multi-meter function Support PoE+, DC12V/2A power out; Replaceable 7.4V/22.2Wh polymer lithium ion battery , which can last 8 hours for normal use; Compatible with more than 30 PTZ protocols(Pelco-D/P, Samsung, Panasonic, Lilin, Yaan,...) Dual LED flashlight</p>		69,000,000
101	<p>DH-PFM905-E</p> <p>4" IPS display, 800*480 resolution, 16.7M colors Support HDCVI/AHD/TVI/CVBS Support RS485 PTZ control Support audio test and digital multi-meter function Support DC12V/1A power out Dual LED torch light Replaceable 7.4V/10.4Wh polymer lithium battery , which can last 5 hours for normal use</p>		37,700,000
02146083954			
			

توجه: دستگاه های جدید XVR(به جز دستگاه های ستاره دار)، دوربین هایی که میکروفون داخلی (Built-in MIC) دارند را پشتیبانی نمی کند. لطفا در انتخاب محصول دقت نمایید.