








































| Turbo HD Camera - DVR | | | | |
|-----------------------|------------------|--|---------------|---|
| Model | Description | Price | Appearance | |
| Entry Level Series | | | | |
| 1080p | | | | |
| 1 | DS-2CE56D0T-IRMM | HD1080p,2MP CMOS Sensor, 12 pcs LEDs, 20m IR, Indoor IR Dome, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, 3.6/6mm Lens | IRR 3,940,000 |  |
| 2 | DS-2CE16D0T-IR | HD1080p,2MP CMOS Sensor, 24 pcs LEDs, 20m IR, Outdoor IR Bullet, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, IP66, 3.6/6mm Lens | IRR 4,560,000 |  |
| 3 | DS-2CE56D0T-IR | HD1080p,2MP CMOS Sensor, 24 pcs LEDs, 20m IR, Outdoor IR Eyeball, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, IP66, 3.6/6mm Lens | IRR 4,350,000 |  |
| 4 | DS-2CE56D0T-IRM | HD1080p,2MP CMOS Sensor, 24 pcs LEDs, 20m IR, Outdoor IR Eyeball, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, IP66, 3.6/6mm Lens | IRR 4,560,000 |  |









| | | | | |
|----|--------------------|---|----------------|---|
| 5 | DS-2CE16D0T-IT1 | HD1080p,2MP CMOS Sensor, 2 pcs EXIR LEDs, 20m IR, Outdoor EXIR Bullet, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, IP66, 3.6/6mm Lens | IRR 5,590,000 |  |
| 6 | DS-2CE16D0T-IT3 | HD1080p,2MP CMOS Sensor, 2 pcs EXIR LEDs, 40m IR, Outdoor EXIR Bullet, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, IP66, 3.6/6/8/12/16mm Lens | IRR 6,130,000 |  |
| 7 | DS-2CE16D0T-IT5 | HD1080p,2MP CMOS Sensor, 4 pcs EXIR LEDs, 80m IR, Outdoor EXIR Bullet, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, IP66, 3.6/6/8/12/16mm Lens | IRR 6,830,000 |  |
| 8 | DS-2CE56D0T-IT1 | HD1080p,2MP CMOS Sensor, 2 pcs EXIR LEDs, 20m IR, Outdoor EXIR Eyeball, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, IP66, 3.6/6mm Lens | IRR 5,090,000 |  |
| 9 | DS-2CE56D0T-IT3 | HD1080p,2MP CMOS Sensor, 2 pcs EXIR LEDs, 40m IR, Outdoor EXIR Eyeball, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, IP66, 3.6/6/8/12/16mm Lens | IRR 5,840,000 |  |
| 10 | DS-2CE16D1T-VFIR3 | HD1080p,2MP CMOS Sensor, 42 pcs IR LEDs, 40m IR, Outdoor IR Vari-focal Bullet, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), IP66, 2.8~12mm Lens | IRR 11,020,000 |  |
| 11 | DS-2CE56D1T-VFIR3 | HD1080p,2MP CMOS Sensor, 42 pcs IR LEDs, 40m IR, Outdoor IR Vari-focal Eyeball, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), IP66, 2.8~12mm Lens | IRR 11,020,000 |  |
| 12 | DS-2CE16D0T-VFIR3E | 2 megapixel highperformance CMOS Analog HD output, up to 1080p resolution Day/Night switch Smart IR Up to 40m IR distance Switchable TVI/AHD/CVI/CVBS-IP66-Lens 2.8 - 12 mm @ F1.4 Angle of view: 102.25° - 32° | IRR 11,290,000 |  |








| | | | | |
|------------------------|--------------------|---|----------------|---|
| 13 | DS-2CE56D0T-VFIR3E | 2 megapixel highperformance CMOS Analog HD output, up to 1080p resolution Day/Night switch Smart IR Up to 40m IR distance Switchable TVI/AHD/CVI/CVBS-IP66-Lens 2.8 - 12 mm @ F1.4 | IRR 11,290,000 |  |
| 14 | DS-2CE16D0T-WL5 | HD 1080p White Supplement Light Bullet Camera 2 Megapixel high-performance CMOS Analog HD output, up to 1080P resolution White supplement light (up to 50 m distance) IP66 Outdoor Lens 2.8/3.6/6mm 24H Color | IRR 8,910,000 |  |
| Starlight Value Series | | | | |
| HD 1080p | | | | |
| 15 | DS-2CE16D8T-ITE | 2M Smart FSI CMOS Sensor, EXIR, 20m IR, Outdoor EXIR Bullet, ICR, 0.005 Lux/F1.2, 12 VDC/built-in PoC, Smart IR, 3D DNR, OSD Menu(Up the Coax), True WDR, IP66, 2.8/3.6/6mm Lens | IRR 9,040,000 |  |
| 16 | DS-2CE56D8T-ITME | 2M Smart FSI CMOS Sensor, EXIR, 20m IR, Outdoor EXIR Eyeball, ICR, 0.005 Lux/F1.2, 12 VDC & built-in PoC, Smart IR, 3D DNR, OSD Menu(Up the Coax), True WDR, IP67, 2.8/3.6/6mm Lens | IRR 9,040,000 |  |
| 17 | DS-2CE16D8T-IT3E | 2M Smart FSI CMOS Sensor, EXIR, 40m IR, Outdoor EXIR Bullet, ICR, 0.005 Lux/F1.2, 12 VDC/built-in PoC, Smart IR, 3D DNR, OSD Menu(Up the Coax), True WDR, IP66, 3.6/6/8/12/16mm Lens | IRR 10,830,000 |  |
| 18 | DS-2CE56D8T-IT1E | 2M Smart FSI CMOS Sensor, EXIR, 20m IR, Outdoor EXIR Eyeball, ICR, 0.005 Lux/F1.2, 12 VDC/built-in PoC, Smart IR, 3D DNR, OSD Menu(Up the Coax), True WDR, IP66, 2.8/3.6/6mm Lens | IRR 9,490,000 |  |
| 19 | DS-2CE16D8T-IT3Z | HD1080p, 2MP CMOS Sensor, EXIR, 40m IR, Outdoor EXIR Motorized Vari-focal Bullet, ICR, 0.005 Lux/F1.2, 12 VDC, Smart IR, 3D DNR, OSD Menu(Up the Coax), True WDR, IP66, 2.8~12mm Motorized Vari-focal Auto-Focus Lens | IRR 18,070,000 |  |

| | | | | |
|-----------------------------|-------------------|--|----------------|---|
| 20 | DS-2CE16D8T-IT3ZE | 2 MP high performance COMS Ultra-Low Light 1920 × 1080 resolution Auto focus, 2.8 mm to 12 mm motorized vari-focal lens 120 dB true WDR, 3D DNREXIR 2.0, Smart IR, up to 40 m IR distance IP67 PoC.atUp the Coax (HIKVISION-C) | IRR 18,070,000 |  |
| Exir Turbo HD Series | | | | |
| 3Mp | | | | |
| 21 | DS-2CE16F1T-IT | 3MP, 3MP CMOS Sensor, 18fps at 1920*1536 resolution, EXIR, 20m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu (Up the Coax), IP66, 2.8/3.6/6mm Lens | IRR 5,330,000 |  |
| 22 | DS-2CE56F1T-ITM | 3MP, 3MP CMOS Sensor, 18fps at 1920*1536 resolution, EXIR, 20m IR, Outdoor EXIR Eyeball, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu (Up the Coax), IP66, 2.8/3.6/6mm Lens | IRR 5,330,000 |  |
| 23 | DS-2CE16F1T-IT1 | 3MP, 3MP CMOS Sensor, 18fps at 1920*1536 resolution, EXIR, 20m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu (Up the Coax), IP66, 2.8/3.6/6mm Lens | IRR 6,010,000 |  |
| 24 | DS-2CE16F1T-IT3 | 3MP, 3MP CMOS Sensor, 18fps at 1920*1536 resolution, EXIR, 40m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu (Up the Coax), IP66, 3.6/6/8/12/16mm Lens | IRR 6,530,000 |  |
| 25 | DS-2CE16F1T-IT5 | 3MP, 3MP CMOS Sensor, 18fps at 1920*1536 resolution, EXIR, 80m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu (Up the Coax), IP66, 3.6/6/8/12/16mm Lens | IRR 7,230,000 |  |
| 26 | DS-2CE56F1T-IT1 | 3MP, 3MP CMOS Sensor, 18fps at 1920*1536 resolution, EXIR, 20m IR, Outdoor EXIR Eyeball, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu (Up the Coax), IP66, 2.8/3.6/6mm Lens | IRR 5,840,000 |  |








| | | | | |
|-------------|------------------|--|----------------|---|
| 27 | DS-2CE56F1T-IT3 | 3MP,3MP CMOS Sensor, 18fps at 1920*1536 resolution, EXIR, 40m IR, Outdoor EXIR Eyeball, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), IP66, 3.6/6/8/12/16mm Lens | IRR 6,190,000 |  |
| 28 | DS-2CE16F7T-IT3Z | 3MP,3MP CMOS Sensor, 18fps at 1920*1536 resolution, EXIR, 40m IR, Outdoor EXIR Motorized Vari-focal Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), True WDR , IP66, 2.8~12mm Motorized Vari-focal Lens | IRR 22,580,000 |  |
| 29 | DS-2CE56F7T-IT3Z | 3MP,3MP CMOS Sensor, 18fps at 1920*1536 resolution, EXIR, 40m IR, Outdoor EXIR Motorized Vari-focal Eyeball, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), True WDR , IP66, 2.8~12mm Motorized Vari-focal Lens | IRR 22,580,000 |  |
| Exir Series | | | | |
| 5Mp | | | | |
| 30 | DS-2CC52H1T-FITS | 5MP, 12.5fps@5MP, 180° panoramic view, EXIR, 20m IR, Indoor EXIR Fisheye, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, ePTZ, DNR, OSD Menu, Built-in Mic, 1.1mm Lens | IRR 32,510,000 |  |
| 31 | DS-2CE16H1T-IT | 5MP, 20fps@5MP or 25fps(P)/30fps(N) @4MP resolution, EXIR, 20m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), IP66, 2.8/3.6/6mm Lens | IRR 8,820,000 |  |
| 32 | DS-2CE56H1T-ITM | 5MP, 20fps@5MP or 25fps(P)/30fps(N) @4MP resolution, EXIR, 20m IR, Outdoor EXIR Eyeball, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), IP66, 2.8/3.6/6mm Lens | IRR 9,490,000 |  |
| 33 | DS-2CE16H1T-IT3 | 5MP, 20fps@5MP or 25fps(P)/30fps(N) @4MP resolution, EXIR, 40m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), IP66, 3.6/6/8/12/16mm Lens | IRR 10,910,000 |  |







| | | | | |
|----------------------------|------------------|---|----------------|---|
| 34 | DS-2CE56H1T-IT1 | 5MP, 20fps@5MP or 25fps(P)/30fps(N) @4MP resolution, EXIR, 20m IR, Outdoor EXIR Eyeball, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), IP66, 2.8/3.6/6mm Lens | IRR 10,100,000 |  |
| Exir Series - Built in PoC | | | | |
| 5Mp | | | | |
| 35 | DS-2CE16H1T-ITE | 5MP@20fps, 4MP@25fps(P)/30fps(N)(Default), EXIR, 20m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC/built-in PoC, Smart IR, DNR, OSD Menu(Up the Coax), IP66, 2.8/3.6/6mm Lens | IRR 9,490,000 |  |
| 36 | DS-2CE56H1T-ITME | 5MP@20fps, 4MP@25fps(P)/30fps(N)(Default), EXIR, 20m IR, Outdoor EXIR Eyeball, ICR, 0.01 Lux/F1.2, 12 VDC/built-in PoC, Smart IR, DNR, OSD Menu(Up the Coax), IP66, 2.8/3.6/6mm Lens | IRR 9,490,000 |  |
| 37 | DS-2CE16H1T-IT1E | 5MP@20fps, 4MP@25fps(P)/30fps(N)(Default), EXIR, 20m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC/built-in PoC, Smart IR, DNR, OSD Menu(Up the Coax), IP66, 2.8/3.6/6mm Lens | IRR 10,830,000 |  |
| 38 | DS-2CE16H1T-IT3E | 5MP@20fps, 4MP@25fps(P)/30fps(N)(Default), EXIR, 40m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC/built-in PoC, Smart IR, DNR, OSD Menu(Up the Coax), IP66, 3.6/6/8/12/16mm Lens | IRR 11,740,000 |  |
| 39 | DS-2CE16H1T-IT5E | 5MP@20fps, 4MP@25fps(P)/30fps(N)(Default), EXIR, 80m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC/built-in PoC, Smart IR, DNR, OSD Menu(Up the Coax), IP66, 3.6/6/8/12/16mm Lens | IRR 12,640,000 |  |




| | | | | |
|----|-------------------|---|----------------|---|
| 40 | DS-2CE56H1T-IT1E | 5MP@20fps, 4MP@25fps(P)/30fps(N)(Default), EXIR, 20m IR, Outdoor EXIR Eyeball, ICR, 0.01 Lux/F1.2, 12 VDC/built-in PoC, Smart IR, DNR, OSD Menu(Up the Coax), IP66, 2.8/3.6/6mm Lens | IRR 10,830,000 |  |
| 41 | DS-2CE56H1T-IT3E | 5MP@20fps, 4MP@25fps(P)/30fps(N)(Default), EXIR, 40m IR, Outdoor EXIR Eyeball, ICR, 0.01 Lux/F1.2, 12 VDC/built-in PoC, Smart IR, DNR, OSD Menu(Up the Coax), IP66, 3.6/6/8/12/16mm Lens | IRR 11,740,000 |  |
| 42 | DS-2CE16H1T-IT3ZE | 5MP@20fps, 4MP@25fps(P)/30fps(N)(Default), EXIR, 40m IR, Outdoor EXIR Motorized Vari-focal, ICR, 0.01 Lux/F1.2, 12 VDC/built-in PoC, Smart IR, DNR, OSD Menu(Up the Coax), IP66, 2.8~12mm Motorized Vari-focal Lens | IRR 18,960,000 |  |
| 43 | DS-2CE56H1T-IT3ZE | 5MP@20fps, 4MP@25fps(P)/30fps(N)(Default), EXIR, 40m IR, Outdoor EXIR Motorized Vari-focal, ICR, 0.01 Lux/F1.2, 12 VDC/built-in PoC, Smart IR, DNR, OSD Menu(Up the Coax), IP66, 2.8~12mm Motorized Vari-focal Lens | IRR 18,960,000 |  |
| 44 | DS-2CE16H0T-ITF | 5 MP Bullet Camera• 5 Megapixel high-performance CMOS• Analog HD output, up to 5MP resolution• True Day/Night• OSD menu, 2D DNR, DWDR• EXIR technology, up to 20m IR distance • IP67• 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)• Up the Coax(HIKVISION-C) | IRR 7,450,000 |  |
| 45 | DS-2CE16H0T-IT1F | 5 MP Bullet Camera• 5 Megapixel high-performance CMOS• Analog HD output, up to 5MP resolution• True Day/Night• OSD menu, 2D DNR, DWDR• EXIR technology, up to 20m IR distance • IP67• 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)• Up the Coax(HIKVISION-C) | IRR 8,130,000 |  |
| 46 | DS-2CE16H0T-IT3F | 5 MP Bullet Camera• 5 Megapixel high-performance CMOS• Analog HD output, up to 5MP resolution• True Day/Night• OSD menu, 2D DNR, DWDR• EXIR technology, up to 40m IR distance • IP67• 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)• Up the Coax(HIKVISION-C) | IRR 9,040,000 |  |
| 47 | DS-2CE16H0T-IT5F | 5 MP Bullet Camera• 5 Megapixel high-performance CMOS• Analog HD output, up to 5MP resolution• True Day/Night• OSD menu, 2D DNR, DWDR• EXIR technology, up to 80m IR distance • IP67• 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)• Up the Coax(HIKVISION-C) | IRR 9,710,000 |  |



| | | | | |
|------------|-------------------|--|----------------|---|
| 48 | DS-2CE56H0T-ITMF | 5 MP Turret Camera• 5 Megapixel high-performance CMOS• Analog HD output, up to 5MP resolution• True Day/Night• OSD menu, 2D DNR, DWDR• EXIR technology, up to 20m IR distance • IP67 weatherproof• 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)• Up the Coax(HIKVISION-C) | IRR 7,000,000 |  |
| 49 | DS-2CE56H0T-IT1F | 5 MP Turret Camera• 5 Megapixel high-performance CMOS• 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)• True Day/Night• OSD menu, 2D DNR, DWDR• EXIR technology, up to 20m IR distance • IP67 weatherproof• 2560 x 1944 resolution• Up the Coax(HIKVISION-C) | IRR 7,900,000 |  |
| 50 | DS-2CE56H0T-IT3F | 5 MP Turret Camera• 5 Megapixel high-performance CMOS• 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)• True Day/Night• OSD menu, 2D DNR, DWDR• EXIR technology, up to 40m IR distance • IP67 weatherproof• 2560 x 1944 resolution• Up the Coax(HIKVISION-C) | IRR 8,580,000 |  |
| 51 | DS-2CE16H0T-IT3ZF | 5 MP Bullet Camera• 5 Megapixel high-performance CMOS• Analog HD output, up to 5MP resolution• 2.7-13.5mm motorized vari-focal lens• True Day/Night• OSD menu, 2D DNR, DWDR• EXIR technology, up to 40m IR distance • IP67• PoC.at• Up the Coax(HIKVISION-C) | IRR 15,580,000 |  |
| 52 | DS-2CE56H0T-IT3ZF | 5 MP CMOS image sensor-Function: day/night ICR-DNR -D-WDRAGC-BLC-Smart IR-Mirror-Min. Illumination: 0.01Lx-IR distans: 40m-Power supply: DC 12VDCPower consumption: max. 6.3W-Dimensions: 123.86x134.3x110.11mmWeight: 580g-Temperature of work: -40°C~60°C | IRR 15,120,000 |  |
| 8Mp | | | | |
| 53 | DS-2CE18U8T-IT3 | 8.29 Megapixel high-performance CMOS Ultra-low light 3840 x 2160 resolution 2.8 mm, 3.6 mm, 6 mm fixed focal lens 120 dB true WDR, 3D DNR EXIR 2.0, smart IR, up to 60m IR distance IP67 Up the Coax(HIKVISION-C) | IRR 27,090,000 |  |
| 54 | DS-2CE78U8T-IT3 | 8.29 Megapixel high-performance CMOS Ultra-low light 3840 x 2160 resolution 2.8 mm, 3.6 mm, 6 mm fixed focal lens 120 dB true WDR, 3D DNR EXIR 2.0, smart IR, up to 60m IR distance IP67 Up the Coax(HIKVISION-C) | IRR 25,740,000 |  |

Turbo HD PTZ Camera

| | | | | |
|----------------------|----------------------------------|--|----------------|---|
| 55 | DS-2AE5223TI-A(24VAC) | 1/3" CMOS, 1920x1080:30fps, TVI & CVBS dual output, 3D DNR, ICR, Color: 0.05lux/F1.4, B/W:0.005lux/F1.4, Optical Zoom:23x, Focus:4.0-92mm, Digital Zoom:16X, Pan range:360° endless; Tilt range: -15°~90°(Auto Flip), Pan Speed: 0.1° - 400°/s, Tilt Speed: 0.1° -120°/s, Up the Coax, 150m IR | IRR 76,490,000 |  |
| 56 | DS-2AE7230TI-A(24VAC) | 1/2.8" CMOS, 1920x1080:30fps, 3D DNR, ICR, Color: 0.2lux/F1.6, B/W:0.02lux/F1.6, Optical Zoom:30x, Focus:4-120mm, Digital Zoom:16X, Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -120°/s, 120m IR distance, Up the Coax | IRR 97,900,000 |  |
| Turbo HD DVR | | | | |
| 720p/1080p | | | | |
| 57 | DS-7204HQHI-K1 (Turbo HD 4.0) | 4 Turbo HD/AHD/Analog interface input, 4-ch video&1-ch audio input, H.265/H.265+ compression, 1 SATA interface, CH01: 3MP @ 15fps, CH02-04:1920x1080P @ 15 fps/ch , support CVBS output, standalone 1U case | IRR 14,690,000 |  |
| 58 | DS-7208HQHI-K1 (Turbo HD 4.0) | 8 Turbo HD/AHD/Analog interface input, 8-ch video&1-ch audio input, H.265/H.265+ compression, 1 SATA interface, CH01 & 02: 3MP @ 15fps, CH03-08:1920x1080P @ 15 fps/ch , , support CVBS output, standalone 1U case | IRR 20,800,000 |  |
| 59 | DS-7208HQHI-K2 (Turbo HD 4.0) | 8 Turbo HD/AHD/Analog interface input, 8-ch video&1-ch audio input, H.265/H.265+ compression, 2 SATA interfaces, CH01 & 02: 3MP @ 15fps, CH03-08:1920x1080P @ 15 fps/ch , support CVBS output, 380 1U case | IRR 26,170,000 |  |
| 60 | DS-7216HQHI-K1 (Turbo HD 4.0) | 16 Turbo HD/AHD/Analog interface input, 16-ch video&1-ch audio input, H.265/H.265+ compression, 1 SATA interface, CH01-04: 3MP @ 15fps, CH05-16:1920x1080P @ 15 fps/ch, 4K UHD output , support CVBS output, standalone 1U case | IRR 38,000,000 |  |
| 61 | DS-7216HQHI-K2 (Turbo HD 4.0) | 16 Turbo HD/AHD/Analog interface input, 16-ch video&1-ch audio input, H.265/H.265+ compression, 2 SATA interfaces, CH01-04: 3MP @ 15fps, CH05-16:1920x1080P @ 15 fps/ch, 4K UHD output , support CVBS output, 380 1U case | IRR 45,380,000 |  |
| 1080p/3Mp/5Mp | | | | |

| | | | | |
|-----------------------------------|------------------------------------|--|----------------|---|
| 62 | DS-7204HUHI-K1 (Turbo HD 4.0) | 4 Turbo HD/AHD/Analog interface input, 4-ch video&4-ch audio input, 1 SATA interface, H.265/H.265+ compression, 5MP: 12fps, 4MP: 15fps, 3MP: 18fps, 1920x1080P: 25(P)/30(N) fps/ch , alarm I/O: 4/1, support CVBS output, standalone 1U case | IRR 22,140,000 |  |
| 63 | DS-7208HUHI-K1 (Turbo HD 4.0) | 8 Turbo HD/AHD/Analog interface input, 8-ch video&4-ch audio input, 1 SATA interface, H.265/H.265+ compression, 5MP: 12fps, 4MP: 15fps, 3MP: 18fps, 1920x1080P: 25(P)/30(N) fps/ch , 4K UHD output , alarm I/O: 8/4, support CVBS output, standalone 1U case | IRR 33,800,000 |  |
| 64 | DS-7208HUHI-K2 (Turbo HD 4.0) | 8 Turbo HD/AHD/Analog interface input, 8-ch video&4-ch audio input, 2 SATA interface, H.265/H.265+ compression, 5MP: 12fps, 4MP: 15fps, 3MP: 18fps, 1920x1080P: 25(P)/30(N) fps/ch , 4K UHD output , alarm I/O: 8/4, support CVBS output, standalone 1U case | IRR 39,280,000 |  |
| 65 | DS-7216HUHI-K2 (Turbo HD 4.0) | 16 Turbo HD/AHD/Analog interface input, 16-ch video&4-ch audio input, 2 SATA interfaces, H.265/H.265+ compression, 5MP: 12fps, 4MP: 15fps, 3MP: 18fps, 1920x1080P: 25(P)/30(N) fps/ch , 4K UHD output , alarm I/O: 16/4, support CVBS output, 380 1U case | IRR 67,370,000 |  |
| 1080p/3Mp/5Mp Built In PoC | | | | |
| 66 | DS-7204HUHI-K1/P (Turbo HD 4.0) | 4 Turbo HD/AHD/Analog interface input, 4-ch video&4-ch audio input, 1 SATA interface, H.265/H.265+ compression, 5MP: 12fps, 4MP: 15fps, 3MP: 18fps, 1920x1080P: 25(P)/30(N) fps/ch, alarm I/O: 4/1, support CVBS output, standalone 1U case, built-in PoC | IRR 27,040,000 |  |
| 67 | DS-7208HUHI-K2/P (Turbo HD 4.0) | 8 Turbo HD/AHD/Analog interface input, 8-ch video&4-ch audio input, 2 SATA interfaces, H.265/H.265+ compression, 5MP: 12fps, 4MP: 15fps, 3MP: 18fps, 1920x1080P: 25(P)/30(N) fps/ch, 4K UHD output , alarm I/O: 8/4, support CVBS output, 380 1U case, built-in PoC | IRR 49,420,000 |  |
| 8MP Built In PoC | | | | |

| | | | | |
|---------------------------------|----------------|---|-----------------|---|
| 68 | DS-7204HTHI-K1 | <p>4-ch, RCA (2.0 Vp-p, 1 KΩ)-4-chBNC interface (1.0 Vp-p, 75 Ω), supporting coaxitron connection-2-ch-Up to 8 MP resolution,Supports H.265+/H.265/H.264+/H.264 IP cameras-VGA: 1-ch, 1920 x 1080/60Hz, 1280 x 1024/60Hz, 1280 x 720/60Hz, 1024 x 768/60HzHDMI: 1-ch, 4K (3840 x 2160)/30Hz, 2K (2560 x 1440)/60Hz, 1920 x 1080/60Hz, 1280 x1024/60Hz, 1280 x 720/60Hz, 1024 x 768/60Hz-Video Bit Rate: -32 Kbps to 16 Mbps-Stream Type: VidVideo, Video & Audioeo, Video & Audio-Two-way Audio: 1-ch, RCA (2.0 Vp-p, 1 KΩ) (using the 1st audio input)-Audio Output: 1-ch, RCA (Linear, 1 KΩ)-Audio Bit Rate: -64 Kbps</p> | IRR 33,560,000 |  |
| 69 | DS-7208HTHI-K2 | <p>4K H265+ TURBO HD DVR-4-ch, RCA (2.0 Vp-p, 1 KΩ)-Video Compression: H.265+/H.265/H.264+/H.264-Analog Video Input: 8-ch,BNC interface (1.0 Vp-p, 75 Ω), supporting coaxitron connectionAnalog and HD-TVI video input: 8 MP, 5 MP, 4 MP, 3 MP, 1080p30, 1080p25, 720p60, 720p50, 720p30, 720p25IP Video Input: 4-ch,Up to 8 MP resolution,Supports H.265+/H.265/H.264+/H.264 IP-Interface Type: 2 SATA interfacesCapacity: Up to 8 TB capacity for each disk-Alarm Input: 8-Alarm Output: 4</p> | IRR 65,270,000 |  |
| 1080P 32CH | | | | |
| 70 | DS-7332HGHI-SH | <p>32CH HD-TVI /CVBS video input , Upto 32CH IP 2MP Video Input, 4CH Audio Input, Support 4 SATA interfaces each Upto 24 TB capacity; 1 eSATA interface, 1080p@15fps 720p/VGA/WD1/4CIF/CIF@25fps , Support up to 32-ch synchronous Playback at 1080P resolution, Long transmission distance over coax cable, HDMI and VGA output at up to 1920x1080P, H.264 & Dual-stream video compression, TCP/IP, PPPoE, DHCP, EZVIZ Cloud P2P, DNS, DDNS, NTP, SADP, SMTP, SNMP, NFS, iSCSI, UPnP., HTTPS, 3 USB2.0 interfaces, 1000M adaptive Ethernet Interface ,1RS-485 interface, 1 RS-232 interface, 1 RS-485 keyboard interface, Alarm Input/Output; 16/4 CH, -10 oC ~+55 oC, 19-inch rack-mounted 1.5U chassis</p> | IRR 112,200,000 |  |
| 1080p/3Mp/5Mp 32CH/ 24CH | | | | |

| | | | | |
|----|----------------|--|-----------------|---|
| 71 | DS-7224HQHI-K2 | <p>Self-adaptive HDTV/HDCVI/AHD/CVBS signal input Upto 24CH, 1-ch Audio Input, Support 2 SATA Interfaces each Upto 12 TB, H.265+/H.265/H.264+/H.264 encoding and IP Support, Full channel recording at up to 4 MP lite resolution, Support HDTV input:4 MP, 3 MP, 1080p30, The 3 MP signal input is only available for channel 1/2/3/4 , Support AHD input:4 MP, 1080p25, Support HDCVI input: 1080p25, Support CVBS, HDMI/VGA Output 1-ch,4K (3840 × 2160)/30Hz, 4 MP lite@15fps, 1080p@25fps,Long distance transmission over UTP and coaxial cable: max. 800m for 1080p and 1200m for 720p HDTV signal, 16-ch synchronous playback, TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF, 1 USB 2.0 Interface & 1 USB 3.0 Interface, 1000M adaptive Ethernet Interface, 1; standard RS-485 serial interface, -10 °C to +55 °C</p> | IRR 105,100,000 |  |
| 72 | DS-7232HQHI-K2 | <p>Self-adaptive HDTV/HDCVI/AHD/CVBS signal input Upto 32CH, 1-ch Audio Input, Support 2 SATA Interfaces each Upto 12 TB, H.265+/H.265/H.264+/H.264 encoding and IP Support, Full channel recording at up to 4 MP lite resolution, Support HDTV input:4 MP, 3 MP, 1080p30, The 3 MP signal input is only available for channel 1/2/3/4 , Support AHD input:4 MP, 1080p25, Support HDCVI input: 1080p25, Support CVBS, HDMI/VGA Output 1-ch,4K (3840 × 2160)/30Hz, 4 MP lite@15fps, 1080p@25fps,Long distance transmission over UTP and coaxial cable: max. 800m for 1080p and 1200m for 720p HDTV signal, 16-ch synchronous playback, TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF, 1 USB 2.0 Interface & 1 USB 3.0 Interface, 1000M adaptive Ethernet Interface, 1; standard RS-485 serial interface, -10 °C to +55 °C</p> | IRR 121,800,000 |  |