



































Network Camera - NVR








	Items	Description	User Price	
20 Series				
1	DS-2CD2020F-I	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (6mm optional), H.264/MJPEG, dual-stream, IP66, DWDR, 3D DNR, BLC, Support on-board storage (SD card not included), IR range: up to 30m, Bracket included, Housing: plastic and metallic, DC12V & external PoE cable, , Support Mobile Monitoring via EZVIZ P2P -W: Built-in Wi-Fi	IRR 16,710,000	
2	DS-2CD2042WD-I	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520: 20fps, 4mm/F2.0 lens (6mm optional), H.264+/H.264/MJPEG, VCA functions, 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR range: up to 30m, Full metallic housing, HIK-Connect cloud service	IRR 23,250,000	
3	DS-2CD2043G0-I	4 MP IR Fixed Bullet Network Camera -1/3" Progressive Scan CMOS 2560 x 1440@30fps 2.8/4/6/8 mm fixed lens Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR H.265+, H.265, H.264+, H.264 Three streams 120dB WDR 2 Behavior analyses, and face detection -BLC/3D DNR/ROI IP67 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB 3-Axis adjustment	IRR 21,450,000	
4	DS-2CD2052-I	1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920: 20fps, 4mm/F2.0 lens (6mm optional), H.264+/H.264/MJPEG, 3 streams, IP67, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 30m, Full metallic housing, HIK-Connect cloud service	IRR 24,220,000	
5	DS-2CD2063G0-I	6 MP IR Fixed Bullet Network Camera -1/2.9" Progressive Scan CMOS 3072 x 2048@20 fps 2.8/4/6/8 mm fixed lens Color: 0.01 lux @ (F1.2, AGC ON), 0.028 lux @ (F2.0, AGC ON), 0 lux with IR H.265+, H.265, H.264+, H.264 Behavior analyses 120dB WDR -BLC/3D DNR/ROI IP67 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 25,740,000	







6	DS-2CD2083G0-I	8 MP IR Fixed Bullet Network Camera -1/2.5" Progressive Scan CMOS 3840 x 2160 @ 15 fps 2.8/4/6/8 mm fixed lens Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR H.265+, H.265, H.264+, H.264 Behavior analyses 120dB WDR - BLC/3D DNR/ROI/HLC IP67Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 30,250,000	
21 Series				
7	DS-2CD2120F-I	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (2.8mm, 6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 30m, Support on-board storage (SD card not included), Support Mobile Monitoring via EZVIZ P2P	IRR 16,710,000	
8	DS-2CD2120F-IS	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (2.8mm, 6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 30m, Support on-board storage (SD card not included), Support Mobile Monitoring via EZVIZ P2P -S: Audio/Alarm IO connectors	IRR 16,710,000	
9	DS-2CD2123G0-IS	2 MP IR Fixed Dome Network Camera-• 1/2.8" Progressive Scan CMOS • 1920 x1080@30fps • 2.8/4/6/8mm fixed lens • Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 Lux @ (F2.0, AGC ON), 0 Lux with IR • H.265+, H.265, H.264+, H.264 • Three streams • 120dB WDR- • 2 Behavior analyses, and face detection • BLC/3D DNR/ROI/HLC • IP67, IK10 • Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 21,670,000	
10	DS-2CD2142FWD-I	Up to 4 megapixel high resolution,Dual stream ,2.8mm/4mm/6mm fixed lens , 120dB Wide Dynamic Range,3D Digital Noise Reduction ,DC12V & PoE,Support H.264+,Up to 30m IR range,IP67 weather-proof protection , -S: Audio/Alarm IO	IRR 21,780,000	
11	DS-2CD2142FWD-IS	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520: 20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264+/H.264/MJPEG, VCA functions, 3 streams, IP67, IK10, DC12V & PoE, DWDR, 3D DNR, BLC, support on-board storage up to 128GB(SD card not included), 3-axis adjustment, IR range: up to 30m, Vandal-proof housing, HIK-Connect cloud service -S: Audio/Alarm IO	IRR 23,250,000	
12	DS-2CD2143G0-IS	4 MP IR Fixed Dome Network Camera 1/3" Progressive Scan CMOS, 2688 x1520@30fps, 2.8/4/6/8mm fixed lensColor: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IRH.265+, H.265, H.264+, H.264, Three streams, 120dB WDR, 2 Behavior analyses, and face detection, BLC/3D DNR/ROI, IP67,IK10, Built-in micro SD/SDHC/SDXC card slot, up to 128 GB, 3-Axis adjustment	IRR 23,480,000	








13	DS-2CD2152F-IS	1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920: 20fps, 4mm/F2.0 lens (6mm optional), H.264+/H.264/MJPEG, 3 streams, IP67, IK10, DC12V & PoE, DWDR, 3D DNR, BLC, support on-board storage up to 128GB(SD card not included), 3-axis adjustment, IR range: up to 30m, Vandal-proof housing, HIK-Connect cloud service -S: Audio/Alarm IO	IRR 25,480,000	
14	DS-2CD2163G0-I	6 MP IR Fixed Dome Network Camera -1/2.9" Progressive Scan CMOS 3072 x 2048@20 fps 2.8/4/6/8 mm fixed lens Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR H.265+, H.265, H.264+, H.2642 Behavior analyses 120dB WDR -BLC/3D DNR/ROI IP67Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 27,990,000	
15	DS-2CD2183G0-I	8 MP IR Fixed Dome Network Camera -BLC/3D DNR/ROI IP67, IK10Built-in micro SD/SDHC/SDXC card slot, up to 128 GB 1/2.5" Progressive Scan CMOS 3840 x 2160 @ 15 fps 2.8/4/6/8 mm fixed lens Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR H.265+, H.265, H.264+, H.2642 Behavior analyses 120dB WDR	IRR 32,960,000	
23 Series				
16	DS-2CD2342FWD-I	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, EXIR range: up to 30m	IRR 22,210,000	
17	DS-2CD2352-I	1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920:20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264+/H.264/MJPEG, 3 streams, IP67, DC12V & PoE, DWDR, 3D DNR, BLC, EXIR range: up to 30m	IRR 33,190,000	
Easy IP Lite Series				
18	DS-2CD1123G0-I	2MP dome Exir, fixed lens 2.8mm,white color-1/2.8" progressive scan CMOS 3D DNR (Digital Noise Reduction)1920 x 1080@30fps Up to 30 m IR range2.8 mm/4 mm/6 mm fixed lens PoE (Power over Ethernet)H.265+, H.265, H.264+, H.264IP67, IK10Dual streamDigital WDR (Wide Dynamic Range)	IRR 13,780,000	
19	DS-2CD1023G0-I	2.0 MP IR Network Bullet Camera-1/2.8" progressive scan CMOS 3D DNR (Digital Noise Reduction)1920 x 1080@30fps Up to 30 m IR range2.8 mm/4 mm/6 mm fixed lens PoE (Power over Ethernet)H.265+, H.265, H.264+, H.264IP67Dual streamDigital WDR (Wide Dynamic Range)	IRR 12,870,000	







20	DS-2CD1043G0-I	4.0 MP IR Network Bullet Camera, 1/3" progressive scan CMOS , 3D DNR (Digital Noise Reduction), 2560 × 1440@20fps Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264 , IP67, Dual stream, Digital WDR (Wide Dynamic Range)	IRR 17,600,000	
21	DS-2CD1143G0-I	4.0 MP IR Network Dome Camera, 1/3" progressive scan CMOS 3D DNR (Digital Noise Reduction), 2560 × 1440@20fps Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens ,PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264IP67, IK10, Dual stream, Digital WDR (Wide Dynamic Range)	IRR 18,510,000	
22	DS-2CD1623G0-IZ	Bullet Network camera 2MP, 2.8-12mm varifocal lens, EXIR, microSD1/2.8" progressive scan CMOSBLC/3D DNR/ROI1920 × 1080@30fpsUp to 30 m IR rangelP672.8 mm to 12 mm varifocal lensDigital WDRH.265+, H.265, H.264+, H.264Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 LuxBuilt-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 29,350,000	
23	DS-2CD1623G0-I	2MP (1920 × 1080) Vari-focal IR Bullet Network CameraSPECIFICATIONS2MP HD1080P 1/2.8" Progressive Scan CMOS1920 × 1080@30fps (N)2.8-12mm VF lens IR range: Up to 30m	IRR 26,180,000	
24	DS-2CD1643G0-I	4 MP EXIR VF Bullet Network Camera, 1/3" progressive scan CMOS BLC/3D DNR/ROI, 2560 × 1440@20fps ,Up to 30 m IR range, 2.8 mm to 12 mm varifocal lens, IP67, H.265+, H.265, H.264+, H.264 120 dB WDR, Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux@ (F1.6, AGC ON), Built-in micro SD/SDHC/SDXC card slot,up to 128 GB	IRR 31,610,000	
25	DS-2CD1723G0-I	1/2.8" progressive scan CMOS 3D DNR (Digital Noise Reduction) 1920 × 1080@30fps Up to 30 m IR range 2.8 mm to 12 mm manual/motorized (with -Z) vari-focal lens PoE (Power over Ethernet) IP67, IK10 H.265+, H.265, H.264+, H.264Dual stream Digital WDR (Wide Dynamic Range)	IRR 26,180,000	
26	DS-2CD1743G0-I	4.0 MP VF Network Bullet Camera, 1/3" progressive scan CMOS 3D DNR (Digital Noise Reduction), 2560 × 1440@20fps Up to 30 m IR range, 2.8 mm to 12 mm manual/motorized (with-Z) vari-focal lens, PoE (Power over Ethernet), IP67, H.265+, H.265, H.264+, H.264, Dual stream, 120 dB WDR (Wide Dynamic Range)	IRR 28,440,000	
24 Series				
27	DS-2CD2420F-IW	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (2.8mm, 6mm optional), H.264/MJPEG, dual-stream, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 10m, Support on-board card slot (SD card not included), Support Mobile Monitoring via EZVIZ P2P -W: Built-in Wi-Fi with WPS	IRR 16,710,000	







28	DS-2CD2442FWD-IW	1/3" Progressive CMOS, ICR, 0.01lux/F1.2, 2688x1520:20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams,DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR range: up to10m, support on-board storage up to 128GB(SD card not included), built-in WIFI	IRR 23,030,000	
25 Series				
29	DS-2CD2520F	Up to 2 megapixel (1920 × 1080 @ 30 fps) resolution,Standard video compression with high compression ratio,Progressive scan CMOS,PoE (Power over Ethernet),Built-in Micro SD/SDHC/SDXC card slot, up to 64 GB ,3D Digital Noise Reduction	IRR 17,160,000	
30	DS-2CD2542FWD-IS	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F2.0 lens (2.8mm, 6mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 10m, support on-board storage up to 128GB(SD card not included), HIK-Connect cloud service -S: Built-in MIC, audio/alarm IO	IRR 31,270,000	
31	DS-2CD2563G0-IS	6 MP IR Fixed Mini Dome Network Camera • 3072 × 2048@20fps • IR: up to 10 m • H.265, H.265+ • 120dB WDR • Built-in Micro SD/SDHC/SDXC slot, up to 128 GB • PoE • EXIR	IRR 35,210,000	
26 Series				
32	DS-2CD2620F-I	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8–12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Support Mobile Monitoring via EZVIZ P2P	IRR 28,900,000	
33	DS-2CD2643G0-IZS	4 MP IR VF Bullet Network Camera - 1/3" Progressive Scan CMOS • 2688 × 1520@30fps • 2.8 to 12 mm varifocal lens • Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with I • H.265+, H.265, H.264+, H.264 • Three streams • 120dB WDR • 2 Behavior analyses, and face detection • BLC/3D DNR/ROI • IP67, IK10• Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 47,410,000	
34	DS-2CD2663FG0-IZS	BLC/3D DNR/ROI IP67, IK10Built-in micro SD/SDHC/SDXC card slot, up to 128 GB 1/2.9" Progressive Scan CMOS 3072 × 2048@20 fps 2.8 to 12 mm varifocal lens Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR H.265+, H.265, H.264+, H.2642 Behavior analyses	IRR 54,630,000	









35	DS-2CD2663G0-IZS	6 MP IR Vari-focal Bullet Network Camera • 1/2.9" Progressive Scan CMOS • 3072 x2048@20fps • 2.8 to 12 mm varifocal lens • Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR • H.265+, H.265, H.264+, H.264 • 120dB WDR • 2 Behavior analyses, and face detection • BLC/3D DNR/ROI • IP67, IK10 • Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 54,630,000	
36	DS-2CD2683G0-IZS	8 MP(4K) IR Vari-focal Bullet Network Camera-• 1/2.5" Progressive Scan CMOS • 3840 x2160@15fps • 2.8 to 12 mm varifocal lens • Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR• H.265+, H.265, H.264+, H.264 • 120dB WDR • 2 Behavior analyses, and face detection • BLC/3D DNR/ROI • IP67, IK10	IRR 63,210,000	
27 Series				
37	DS-2CD2720F-I	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8-12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Vandal-proof, Support Mobile Monitoring via EZVIZ P2P	IRR 25,040,000	
38	DS-2CD2720F-IZ	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8-12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Vandal-proof, Support Mobile Monitoring via EZVIZ P2P-Z: Motorized VF lens	IRR 37,470,000	
39	DS-2CD2742FWD-IZS	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 2.8-12mm VF lens, IP67, H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 128GB (SD card not included), Vandal-proof housing, HIK-Connect cloud service -S: Audio/alarm IO -Z: Motorized VF lens	IRR 45,960,000	
40	DS-2CD2723G0-IZS	2MP IR Motorized NETWORK DOME CAMERA 1/2.8" 2MP progressive scan CMOS Up to 1920 x 1080 resolution (25 fps) 2.8-12 mm Motorized lens , 0 lux IR on Max IR distance: 30 meters H.265+,H.265,H.264+,H.264,MJPEG video compression 3DDNR,BLC, WDR(120dB),ROI,VCA,Micro SD (Up to 128 GB), Reset Button 1 Audio I/O , 1 Alarm I/O PoE, DC12V, IP67,IK10,3 axis adjustment Onvif support	IRR 42,900,000	
41	DS-2CD2743G0-IZS	4 MP IR VF Dome Network Camera -BLC/3D DNR/ROI IP67, IK10Built-in micro SD/SDHC/SDXC card slot, up to 128 GB 3-Axis adjustment 1/3" Progressive Scan CMOS 2560 x 1440@30fps 2.8 to 12 mm Varifocal lens Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR H.265+, H.265, H.264+, H.264Three streams 120dB WDR 2 behavior analyses, and face detection -WDR-Day & Night IR Cut Filter Digital Noise Reduction 3D DNR	IRR 47,410,000	










42	DS-2CD2763G0-IZS	6 MP IR Vari-focal Dome Network Camera • 1/2.9" Progressive Scan CMOS • 3072 x2048@20fps • 2.8 to 12 mm varifocal lens • Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR • H.265+, H.265, H.264+, H.264 • 120dB WDR • 2 Behavior analyses, and face detection • BLC/3D DNR/ROI • IP67, IK10 • Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 54,630,000	
43	DS-2CD2783G0-IZS	8 MP(4K) IR Vari-focal Dome Network Camera • 1/2.5" Progressive Scan CMOS • 3840 x2160@15fps • 2.8 to 12 mm varifocal lens • Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR • H.265+, H.265, H.264+, H.264 • 120dB WDR • 2 Behavior analyses, and face detection • BLC/3D DNR/ROI • IP67, IK10 • Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 63,210,000	
29 Series				
44	DS-2CD2942F-IS	1/3" Progressive CMOS, Electronic Day/night, Up to 2464 x 1520 resolution, 1.6mm/F1.6 fixed lens, 180° Panoramic view, H.264/MJPEG, 3D DNR, DC12V & PoE, Support on-board storage up to 64GB (SD card not included), software de-warping via iVMS5200 or iVMS4200, Support mobile monitoring via HIK-cloud P2P -I: 3pcs IR LEDs, up to 10m IR -S: Audio/Alarm IO -W: Built-in Wi-Fi	IRR 61,030,000	
45	DS-2CD2955FWD-IS	5 MP Network Fisheye Camera, Up to 5 megapixel high resolution, 2560 x 1920 @30fps, H.265, H.265+, H.264+, H.264, Support 14 display modes, FOV: horizontal FOV 180°, vertical FOV 180°, Dual video streams, DC12V & PoE (802.3af), Digital Noise Reduction, Support on-board storage, up to 128 GB, Up to 8m IR range, -S: Audio/Alarm IO	IRR 66,000,000	
2T Series				
46	DS-2CD2T42WD-I5	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F1.4 lens (6mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, HIK-Connect cloud service -I5: 2pcs EXIR LEDs, up to 50m IR range	IRR 28,440,000	
47	DS-2CD2T42WD-I8	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F1.4 lens (6mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, HIK-Connect cloud service -I8: 4pcs EXIR LEDs, up to 80m IR range	IRR 29,960,000	










48	DS-2CD2T43G0-I5	1/3" Progressive Scan CMOS,2688 x1520@30fps,2.8/4/6/8mm fixed lens • Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR, H.265+, H.265, H.264+, H.264,Three streams,120dB WDR,2 Behavior analyses, and face detection,BLC/3D DNR/ROI,IP67,Built-in micro SD/SDHC/SDXC card slot, up to 128 GB-up to 50m IR range	IRR 24,390,000	
49	DS-2CD2T52-I5	1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920:20fps, 4mm/F1.4 lens (6mm optional), H.264+/H.264/MJPEG, 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, HIK-Connect cloud service, 2pcs EXIR LEDs, up to 50m IR range	IRR 32,960,000	
50	DS-2CD2T63G0-I5	6 MP IR Fixed Bullet Network Camera -BLC/3D DNR/ROI IP67Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.9" Progressive Scan CMOS 3072 x 2048@20 fps 2.8/4/6/8 mm fixed lens Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR H.265+, H.265, H.264+, H.2642 Behavior analyses 120dB WDR	IRR 29,350,000	
51	DS-2CD2T63G0-I8	6 MP IR Fixed Bullet Network Camera -BLC/3D DNR/ROI IP67Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.9" Progressive Scan CMOS 3072 x 2048@20 fps 2.8/4/6/8 mm fixed lens Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR H.265+, H.265, H.264+, H.2642 Behavior analyses 120dB WDR - up to 80m IR range	IRR 31,160,000	
52	DS-2CD2T83G0-I5	8 MP IR Fixed Bullet Network Camera - 1/2.5" Progressive Scan CMOS -3840 x 2160 @15 fps 2.8/4/6/8 mm fixed lens Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR H.265+, H.265, H.264+, H.2642 Behavior analyses 120dB WDR .BLC/3D DNR/ROI IP67Built-in micro SD/SDHC/SDXC card slot, up to 128 G	IRR 35,210,000	
53	DS-2CD2T83G0-I8	8 MP IR Fixed Bullet Network Camera - 1/2.5" Progressive Scan CMOS -3840 x 2160 @15 fps 2.8/4/6/8 mm fixed lens Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR H.265+, H.265, H.264+, H.2642 Behavior analyses 120dB WDR .BLC/3D DNR/ROI IP67Built-in micro SD/SDHC/SDXC card slot, up to 128 G-up to 80m IR range	IRR 37,020,000	
2F Series				
54	DS-2CD2F52F-IS	1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920: 20fps,2048x1536: 25fps(P)/30fps(N), 4mm/F2.0 lens (2.8/6mm lens optional), H.264+/H.264/MJPEG, 3 streams, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 10m, Support on-board storage up to 128GB(SD card not included), Pan: 0°~180°, Tilt: 0°~75°, HIK-Connect cloud service -S: Audio/Alarm IO	IRR 24,750,000	
2D Series				










55	DS-2CD2D14WD	1/4" Progressive CMOS, Electronic Day/night, Color: 0.01lux/F1.2, B/W: 0.001lux/F1.2, 1280x720: 25fps(P)/30fps(N), 3.6mm/F1.2 lens, H.264/MJPEG, dual-stream, DC12V, 100dB WDR, 3D DNR, BLC, Support Mobile Monitoring via EZVIZ P2P	IRR 17,270,000	
2E Series				
56	DS-2CD2E20F-W	1/3" Progressive CMOS, Day/night, 0.1lux/F1.2, 1920x1080:25fps(P)/30fps(N), 4mm lens (2.8/6mm optional), H.264/MJPEG, dual-stream, DC12V & PoE, DWDR, 3D DNR, BLC, Support on-board storage up to 64GB (SD card not included), Support Mobile Monitoring via EZVIZ P2P, Color Lens Cover optional (Black, Silver, Golden) -W: Built-in Wi-Fi	IRR 24,610,000	
2Q Series				
57	DS-2CD2Q10FD-IW	1/4" Progressive CMOS, ICR, 0lux with IR, 4mm/F2.0 (2.8/6mm optional), Pan/tilt rotation, 1280x720:25fps(P)/30fps(N), H.264/MJPEG, dual-stream, DC5V, DWDR, 3D DNR, BLC, Support on-board card slot (SD card not included), Audio, Alarm IO, Up to 10m IR, PIR, Wi-Fi with WPS connection, Support Mobile Monitoring via EZVIZ P2P	IRR 22,070,000	
58	DS-2CV2Q21FD-IW	1/2.8" Progressive CMOS, ICR, 0lux with IR, 1920x1080: 25fps(P)/30fps(N), 2.8mm lens, H.264/MJPEG, dual-stream, 3D DNR, 5m IR, PT function (Pan: 0° ~ 355°; Tilt: -10° ~ 90°), support on-board storage up to 128GB, HIK-Connect cloud service, Build-in microphone and speaker, support two-way audio. Built-in Wi-Fi, 12VDC power supply. Default: No SD card included. /32GB-T: Include 16GB sd card.	IRR 19,150,000	
2U Series				
59	DS-2CV2U21FD-IW	1/2.8" Progressive CMOS, ICR, 0lux with IR, 1920x1080: 25fps(P)/30fps(N), 2.8mm lens, H.264/MJPEG, dual-stream, 3D DNR, 5m IR, support on-board storage up to 128GB, HIK-Connect cloud service, Build-in microphone and speaker, support two-way audio. Built-in Wi-Fi, 12VDC power supply. /32GB-T: Include 32GB sd card.	IRR 13,930,000	
IP PTZ Camera				
2" IR PTZ				
60	DS-2CD2202I-DE3	2 MP High Resolution, Compact IR Pan/Tilt/Zoom Camera, 1920 x 1080p HD Real-Time Resolution, 2x Zoom, 16x Digital Zoom, 20 Meters IR Distance, PoE and 12 VDC Power Supply, Built-In Mic, WiFi, MicroSD Card Local Storage, Up to 128 GB, Easy To Install and Adjust	IRR 26,400,000	





61	DS-2DE4A220IW-DE	1/2.8" Progressive Scan CMOS, Up to 1920 x 1080 resolution 20x Optical Zoom, 16x Digital Zoom, WDR, 3D DNR, HLC, Smart IR Up to 50 m IR distance, 12 VDC & PoE+ (802.3at, class4), Support H.265 video compression	IRR 99,340,000	
	4" IR PTZ			
62	DS-2DE4220IW-DE	2MP, 1/3" CMOS sensor, H.264 codec, Color: 0.02lux/F1.5, B/W:0.02lux/F1.5, Optical Zoom:20x, Focus:4.7-94.0mm, Digital Zoom:16X, Pan range:360° endless; Tilt range: -15°~90°(Auto Flip), Pan Speed: 0.1° - 80°/s, Tilt Speed: 0.1° - 80°/s, 100m IR Distance, POE&12VDC	IRR 77,660,000	
	5" IR PTZ			
63	DS-2DE5220IW-AE	H.265+/H.265/H.264+/H.264 ; 2MP, 1/3" CMOS, 3D DNR, ICR, Color: 0.02lux/F1.5, B/W:0.02lux/F1.5, Optical Zoom:20x, Focus:4.7-94.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan range:360° endless; Tilt range: -15°~90°(Auto Flip), Pan Speed: 0.1° -400°/s, Tilt Speed: 0.1° -200°/s, 150m IR Distance, Hi-PoE&24VAC	IRR 129,130,000	
	5" PTZ			
64	DS-2DE5230W-AE	H.265+/H.265/H.264+/H.264 codec, 2MP, 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom 30x, Focus:4.3-129.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -250°/s, Tilt Speed: 0.1° -150°/s	IRR 134,540,000	
	7" IR PTZ			
65	DS-2DE7220IW-AE	H.265+/H.265/H.264+/H.264 codec, 2MP, 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:20x, Focus: 4.7-94.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -120°/s, 150m IR Distance, Hi-PoE&24VAC	IRR 135,450,000	
66	DS-2DE7230IW-AE	H.265+/H.265/H.264+/H.264 codec, 2MP, 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:30x, Focus:4.3-129.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -120°/s, 150m IR Distance, Hi-PoE&24VAC	IRR 156,680,000	

67	DS-2DE7320IW-AE	1/2.8" Progressive Scan CMOS ,2048 × 1536@30fps Resolution,20x optical zoom, 16x digital zoom ,WDR ,3D Positioning ,24VAC & Hi-PoE,Up to 150m IR distance	IRR 177,180,000	
68	DS-2DE7420IW-AE	1/1.9" progressive scan CMOS,Up to 2560 × 1440 resolution,20x Optical Zoom, 16x Digital Zoom,Defog, EIS, 3D DNR, BLC, HLC, Digital WDR,IR distance up to 150 m,24 VAC & Hi-PoE,Support H.265+/H.265 video compression	IRR 187,830,000	
69	DS-2DE7430IW-AE	1/1.9" progressive scan CMOS,Up to 2560 × 1440 resolution,30x Optical Zoom, 16x Digital Zoom,Defog, EIS, 3D DNR, BLC, HLC, Digital WDR,IR distance up to 150 m,24 VAC & Hi-PoE,Support H.265+/H.265 video compression	IRR 206,270,000	
70	DS-2DE7530IW-AE	H.265+/H.265/H.264+/H.264 codec, 2MP, 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:20x, Focus: 4.7-94.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -120°/s, 150m IR Distance, Hi-PoE&24VAC	IRR 231,150,000	
PanoVu Mini Series IR Network PTZ Camera				
71	DS-2PT3326IZ-DE3 (2.8-12mm)	H.2Panoramic Camera:1/2.8" progressive scan CMOS,3-ch1920 × 1080@30fps resolution,Min. illumination: Color: 0.05 Lux @(F2.0, AGC ON),B/W: 0.01 Lux @(F2.0, AGC ON),0 Lux with IR, Support H.265 video compression, Horizontal FOV: 128.5° × 3PTZ Camera:1/2.8" progressive scan CMOS,Up to 1920 × 1080@30fps resolution,Min. illumination:Color: 0.05 Lux @(F2.0, AGC ON), B/W: 0.01 Lux @(F2.0, AGC ON), 0 Lux with IRSupport H.265 video compression,4x optical zoom, 8x digital zoom	IRR 102,920,000	
Network Camera - NVR				
72	DS-7604NI-E1	40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interface, standalone 1U case	IRR 14,690,000	
73	DS-7604NI-E1/4P	40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interfaces, 4 independent PoE network interfaces, standalone 1U case	IRR 21,010,000	
74	DS-7604NI-Q1	IP video input 4-ch,Up to 8 MP resolution,Incoming bandwidth 40 Mbps , Outgoing bandwidth 80 Mbps , Audio output 1-ch,Decoding format H.265/H.265+/H.264/H.264+/MPEG4, 1 SATA interfaceCapacity Up to 6TB capacity for each disk,	IRR 16,500,000	

75	DS-7604NI-Q1/4P	IP video input 4-ch,Up to 8 MP resolution,Incoming bandwidth 40 Mbps , Outgoing bandwidth 80 Mbps , Audio output 1-ch,Decoding format H.265/H.265+/H.264/H.264+/MPEG4, 1 SATA interfaceCapacity Up to 6TB capacity for each disk, 4 independent PoE network interfaces	IRR 23,040,000	
76	DS-7604NI-K1	40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interface, standalone 1U case	IRR 16,500,000	
77	DS-7604NI-K1/4P	40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interfaces, 4 independent PoE network interfaces, standalone 1U case	IRR 23,040,000	
78	DS-7608NI-Q1	IP video input 8-ch,Up to 8 MP resolution,Incoming bandwidth 80 Mbps , Outgoing bandwidth 80 Mbps , Audio output 1-ch,Decoding format H.265/H.265+/H.264/H.264+/MPEG4, 1 SATA interfaceCapacity Up to 6TB capacity for each disk,	IRR 22,840,000	
79	DS-7608NI-Q1/8P	IP video input 8-ch,Up to 8 MP resolution,Incoming bandwidth 80 Mbps , Outgoing bandwidth 80 Mbps , Audio output 1-ch,Decoding format H.265/H.265+/H.264/H.264+/MPEG4, 1 SATA interfaceCapacity Up to 6TB capacity for each disk,8 independent PoE network interfaces	IRR 37,060,000	
80	DS-7608NI-Q2	IP video input 8-ch,Up to 8 MP resolution,Incoming bandwidth 80 Mbps , Outgoing bandwidth 80 Mbps , Audio output 1-ch,Decoding format H.265/H.265+/H.264/H.264+/MPEG4, 2 SATA interfaceCapacity Up to 6TB capacity for each disk,	IRR 25,180,000	
81	DS-7608NI-E1	80Mbps Bit Rate Input Max (up to 8-ch IP video), 1 SATA interfaces, 380 1U case	IRR 18,740,000	
82	DS-7608NI-E2	80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 380 1U case	IRR 20,560,000	
83	DS-7608NI-E2/8P	80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 8 independent PoE network interfaces, 380 1U case	IRR 33,130,000	

84	DS-7608NI-K2	80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 380 1U case, alarm I/O: 4/1(optional)	IRR 25,180,000	
85	DS-7608NI-K2/8P	80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 8 independent PoE network interfaces, 380 1U case, alarm I/O: 4/1(optional)	IRR 39,860,000	
86	DS-7616NI-E2	160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 380 1U case	IRR 22,660,000	
87	DS-7616NI-Q1	IP video input 16-ch, Incoming bandwidth 160 Mbps Outgoing bandwidth 80 Mbps, 1 SATA interfaces ,Two-way audio 1-ch	IRR 23,760,000	
88	DS-7616NI-Q2/16P	IP video input 16-ch, Incoming bandwidth 160 Mbps Outgoing bandwidth 80 Mbps, 2 SATA interfaces ,Two-way audio 1-ch, 16 independent PoE network interfaces	IRR 52,800,000	
89	DS-7616NI-E2/8P	160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 8 independent PoE network interfaces, 380 1U case	IRR 34,740,000	
90	DS-7616NI-E2/16P	160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 16 independent PoE network interfaces, 380 1U case	IRR 46,490,000	
91	DS-7616NI-K2	160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 380 1U case, alarm I/O: 4/1(optional)	IRR 27,280,000	
92	DS-7616NI-K2/16P	160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 16 independent PoE network interfaces, 380 1U case, alarm I/O: 4/1(optional)	IRR 52,800,000	

93	DS-7716NI-E4	160Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 1.5U case,19"	IRR 49,420,000	
94	DS-7716NI-E4/16P	160Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, 16 independent PoE network interfaces, alarm I/O: 16/4, 1.5U case,19"	IRR 74,170,000	
95	DS-7716NI-K4	160Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 1.5U case,19"	IRR 61,070,000	
96	DS-7716NI-K4/16P	160Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, 16 independent PoE network interfaces, alarm I/O: 16/4, 1.5U case,19"	IRR 83,490,000	
97	DS-7732NI-K4	256Mbps Bit Rate Input Max(up to 32-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 1.5U case,19"	IRR 76,920,000	
98	DS-7732NI-K4/16P	256Mbps Bit Rate Input Max(up to 32-ch IP video), 4 SATA Interfaces, 16 independent PoE network interfaces, alarm I/O: 16/4, 1.5U case,19"	IRR 97,850,000	
99	DS-7732NI-E4	200Mbps Bit Rate Input Max(up to 32-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 1.5U case,19"	IRR 64,810,000	
100	DS-7732NI-E4/16P	200Mbps Bit Rate Input Max(up to 32-ch IP video), 4 SATA Interfaces, 16 independent PoE network interfaces, alarm I/O: 16/4, 1.5U case,19"	IRR 88,470,000	
101	DS-7104NI-E1/M	4-ch, 1-ch, RCA (2.0 Vp-p, 1kΩ) ,40 Mbps,4 MP/3 MP/1080p/1.3 MP/UXGA/720p/VGA/4CIF /DCIF/2CIF/CIF/QCIF ,Main stream: 50 fps (P)/60 fps (N), sub-stream: 50 fps (P)/60 fps (N)	IRR 13,960,000	

102	DS-7108NI-E1/M	4-ch, 1-ch, RCA (2.0 Vp-p, 1kΩ) ,40 Mbps,4 MP/3 MP/1080p/1.3 MP/UXGA/720p/VGA/4CIF /DCIF/2CIF/CIF/QCIF ,Main stream: 50 fps (P)/60 fps (N), sub-stream: 50 fps (P)/60 fps (N)	IRR 17,540,000	
All In One Series				
103	DS-7600NI-E1/A/1T	80Mbps Bit Rate Input Max (up to 8-ch IP video), 1 SATA interface, 22 inch monitor, 1TB HDD WD10JUCT pre-installed	IRR 69,190,000	
Network Cables				
104	DS-1LN5E-S	UTP / CAT.5e / Indoor PVC / 24AWG Full 305m OFC / 0.50mm CM Rating Default Color: Grey	IRR 12,220,000	
105	DS-1LN6-UU	UTP / CAT.6 / Indoor PVC / 23AWG Full 305m OFC / 0.565mm CM Rating Default Color: Orange	IRR 14,380,000	
Network Cables				
106	DS-1602ZJ	Wall mount , Hik white , Aluminum alloy , 97×182×305mm Suitable for: DS-2DE/AE4xxx DS-2DE/AE5xxx DS-2DE/AE7xxx DS-2DF8xxx DS-2DF6xxx DS-2DF7xxx DS-2DF5xxx	IRR 2,410,000	